









Star with glossy finish   Black with matte finish   Desert Sand watte finis
Star with glossy finish   Black ith matte finish   Desert Sand natte finish   Desert Sand natte finish    nium Low Step    stour Mobie E25 Air 75mm    AZX-5811.5" SHIS With ock 150° Integrated Cables    NO Steps E6100 60Nm    n 36V - Integrated on Downtube wable    to 100km
Star with glossy finish   Black ith matte finish   Desert Sand natte finish  nium Low Step  Itour Mobie E25 Air 75mm  AZX-581 1.5" SHIS With ock 150° Integrated Cables  INO Steps E6100 60Nm  n 36V - Integrated on Downtube ovable to 100km
ith matte finish   Desert Sand natte finish  nium Low Step  Itour Mobie E25 Air 75mm  AZX-581 1.5" SHIS With sick 150° Integrated Cables  INO Steps E6100 60Nm  n 36V - Integrated on Downtube syable to 100km
ith matte finish   Desert Sand natte finish  nium Low Step  Itour Mobie E25 Air 75mm  AZX-581 1.5" SHIS With sick 150° Integrated Cables  INO Steps E6100 60Nm  n 36V - Integrated on Downtube syable to 100km
ith matte finish   Desert Sand natte finish  nium Low Step  Itour Mobie E25 Air 75mm  AZX-581 1.5" SHIS With sick 150° Integrated Cables  INO Steps E6100 60Nm  n 36V - Integrated on Downtube syable to 100km
nium Low Step  tour Mobie E25 Air 75mm  AZX-581 1.5" SHIS With ock 150° Integrated Cables  NO Steps E6100 60Nm on 36V - Integrated on Downtube ovable to 100km
AZX-581 1.5" SHIS With the sk 150° Integrated Cables  NO Steps E6100 60Nm  n 36V - Integrated on Downtube to 100km
AZX-581 1.5" SHIS With sck 150° Integrated Cables NO Steps E6100 60Nm n 36V - Integrated on Downtube ovable to 100km
ock 150° Integrated Cables NO Steps E6100 60Nm n 36V - Integrated on Downtube ovable to 100km
ock 150° Integrated Cables NO Steps E6100 60Nm n 36V - Integrated on Downtube ovable to 100km
NO Steps E6100 60Nm n 36V - Integrated on Downtube ovable to 100km
n 36V - Integrated on Downtube ovable to 100km
n 36V - Integrated on Downtube ovable to 100km
ovable to 100km
hours total charge time
hours total charge time
NO SC-E6100
0mm / 31.8mm (Straight)
nm - adjustable 0-90° - with ated cables
I GA30
NENTAL RaceKing 29''x 2,2''
ouble Wall 25mm
Stainless Steel
NO HB-MT400 100 Thru-axle
NO Deore M6000 135mm
NO Hydraulic MT200
NO SM-RT10 180mm
NO SM-RT10 180mm
NO Deore M5100
NO Deore CS-M5100-11 11-51T
NO Deore 11S
NO SM-CRE61 38T
NO FC-E6100 175mm
KMC E11 Turbo e-bike series
HIMANO
VELO Tour AVS (max.: 25Kg)
IINGA Axendo 40 with reflector
DILLY with reflector
VELO Dux
desired and the second
cluded. Sold separately. ROYAL Essenza Moderate Black
ck 350mm 31,6mm/15mm
·
lack with quick release
·
NOCOLINIO NECOLINIO NECOLI

<sup>\*</sup> We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.