



**C800 Urban Motion** £ 2,149





S (44cm) - M (49cm) - L (54cm)			
	M (50cm) - L (55cm)	S/M (46cm) - L/XL (54cm)	S (46cm) - M (52cm) - L (56cm)
Approx. 28kg	Approx. 28kg	Approx. 26,5kg	Approx. 24kg
190Kg	120kg	145kg	145kg
Powder Painting Scratch Resistant	Powder Painting Scratch Resistant	1.0.09	Powder Painting Scratch Resistant
with Matte or Glossy Varnish	with Matte or Glossy Varnish	-	With Matte Varnish
Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish	Black Suit with matte finish	White Star with glossy finish   Happy Blue with matte finish   Black Suit with matte finish   Desert Sand with matte finish	
Low Step Aluminium	Aluminium Low Step	Aluminium High Step	Aluminium Low Step
Sr Suntour Raindon 34 Air Travel	-	Sr SUNTOUR Mobie E25 Air 75mm	-
-	Rigid Allov 28"	-	Rigid Alloy 28"
FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	ACROS AZX-5811.5" SHIS With Blocklock 150º Integrated Cables	SHIS 1-1/8"
		blocklock 130 integrated cables	
BROSE DRIVE S MAG Horizontal QONIM	BROSE DRIVE C Horizontal 50Nm	SHIMANO Steps F6100 60Nm	BAFANG H400B Rear Wheel 45Nm
522Wh 36V - Down Tube Integration -	504Wh 36V - Semi-Integrated on	504Wh 36V - Integrated on Downtube	360Wh 36V - Integrated on Downtube - Non Removable
			40km to 100km
			-
			2A - 5 hours total charge time
с	, , , , , , , , , , , , , , , , , , ,		BAFANG DP.C11
E. COLE / III OLITA		5.11-1/10-50-E0100	5, 1, 1110 D1.011
AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)
AL 50mm - 31.8mm - 0º	AL 90mm - 31.8mm - adjustable 0- 90º	AL 90mm - 31.8mm - adjustable 0- 90° with Cable Integration	AL 90mm - 31.8mm - adjustable 0- 90º
ERGON GA30	ERGOTECH EG-AMBITION	ERGON GA30	HERRMANS DD36 Ergonomic
CONTINENTAL Mountain king 27,5"x2,6" (Tubeless Ready)	CONTINENTAL Ride Cruiser 28''x2,2''	CONTINENTAL RaceKing 29"x2,2"	CONTINENTAL Contact Cruiser 28''x2,0''
27,5"	28"	29''	28"
Alloy Double Wall 30mm (Tubeless Ready)	Alloy Double 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
Black Stainless Steel	Black Stainless Steel	Black Stainless Steel	Stainless Steel
SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru Axle 15mm	SHIMANO HB-TX506 9x100mm QR
SHIMANO Deore M6000 135mm	SHIMANO NEXUS SG-C6001 135mm	SHIMANO Deore M6000 135mm	BAFANG H400B 135mm
SHIMANO Hydraulic MT/00	CLARKS Hydraulic M2		ALHONGA Hydraulic HJ-HT474
,	,	,	ALHONGA HJ-DXR1806 180MM
			ALHONGA HJ-DXR1806 180MM
	-		SHIMANO Altus 9S
	-		SHIMANO Altus 9S 11-36T
	SHIMANO NEXUS 8		SHIMANO Altus 9S
			MIRANDA ChainFlow BCD104 38T
		SHIMAN0 FC-E6100 175mm	MIRANDA JIS 170
KMC E11 Turbo e-bike series	SHIMANO CN-NX10	KMC E11 Turbo e-bike series	SHIMANO CN-HG53
Yes - FSA	Yes - HEBIE	Yes - FSA	Yes - SKS
ATRANIVELO Tour AVS (max : 25Kg)	ATRANVELO City AVS (max · 25Kg)	ATRANIVELO Tour AVS (max · 25Kg)	ATRANVELO City AVS (max.: 25Kg)
	,		AXA Ecoline 15 with reflector
			AXA Slim with reflector
			ATRANVELO Dux
		-	SKS
Yes	Yes	-	-
	Not included. Sold separately.	- Not included. Sold separately.	- Not included. Sold separately.
NOT INCLUDED. SOLD SENARATELY		· · · ·	
Not included. Sold separately.	SELLE ROYAL Rin Gel	SELLE RUYAL ESSENZA MODERATE	
SELLE ROYAL Essenza Moderate Gel	SELLE ROYAL Rio Gel AL Black 350mm 272mm/15mm	SELLE ROYAL Essenza Moderate Gel	SELLE ROYAL Rio Gel AL Black 300mm 316mm/15mm
SELLE ROYAL Essenza Moderate Gel AL Black 350mm 31,6mm/15mm	AL Black 350mm 27.2mm/15mm	AL Black 350mm 31,6mm/15mm	AL Black 300mm 31,6mm/15mm
SELLE ROYAL Essenza Moderate Gel			
	<ul> <li>with Matte or Glossy Varnish</li> <li>Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish</li> <li>Low Step Aluminium</li> <li>Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5''</li> <li>-</li> <li>FSA 1.5" to 1-1/8" Tapered SHIS</li> <li>BROSE DRIVE S MAG Horizontal 90Nm</li> <li>522Wh 36V - Down Tube Integration - Removable</li> <li>40km to 100km</li> <li>Yes</li> <li>4A - 3 to 6 hours total charge time</li> <li>BROSE Allround</li> <li>AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)</li> <li>AL 50mm - 31.8mm - 0°</li> <li>ERGON GA30</li> <li>CONTINENTAL Mountain king 27,5"×2,6" (Tubeless Ready)</li> <li>27,5"</li> <li>Alloy Double Wall 30mm (Tubeless Ready)</li> <li>Black Stainless Steel</li> <li>SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm</li> <li>SHIMANO Boore 11S 11-51T</li> <li>SHIMANO Deore 11S</li> <li>SHIMANO Deore 11S</li> <li>MIRANDA ChainFlow 3D BCD104 38T</li> <li>SAMOX Shape 170/0</li> <li>KMC E11 Turbo e-bike series</li> </ul>	with Matte or Glossy Varnishwith Matte or Glossy VarnishHock Grey with matte finish   Emerald Green With glossy varnishBlack Suit with matte finishLow Step AluminiumAluminium Low StepSr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5"Rigid Alloy 28"FSA 1.5" to 1-1/8" Tapered SHISFSA 1.5" to 1-1/8" Tapered SHISBROSE DRIVE S MAG Horizontal 90Nm S22Wh 36V - Down Tube Integration S04Wh 36V - Semi-Integrated on Downtube - Removable40km to 100km40km to 100kmYesYes4A - 3 to 6 hours total charge time Straight) FSA V-Drive 740mm / 318mm (Straight)AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)AL 50mm - 31.8mm - 0°Al 660mm / 31.8mm (Curved)CONTINENTAL Mountain King 27,5"x2,6" (Tubeless Ready)CONTINENTAL Ride Cruiser 28"x2,2"27,5"28"Alloy Double Wall 30mm (Tubeless Ready)Black Stainless SteelSHIMANO Hg-MT400-B Boost 110 SHIMANO Hg-MT400-100 Thru-axle 15mmSHIMANO Deore 115-SHIMANO	with Matte or Glossy Varnish     with Matte or Glossy Varnish     -       Hock Grey with matte finish   Dark With glossy varnish     Black Suit with matte finish with glossy varnish     White Star with glossy finish   Happy Blue with matte finish   Black Suit with matte finish matte finish   Desert Sand with matte finish       Low Step Aluminium     Aluminium Low Step     Aluminium High Step       Sr Suntour Raindon 34 Air Travel 120mm Avle Boost 110mm 27.5*     -     Sr SUNTOUR Mobie E25 Air 75mm       -     Rigid Alloy 28*     -       FSA 15* to 1-1/8* Tapered SHIS     FSA 15* to 1-1/8* Tapered SHIS     SHIMANO Steps E6100 60Nm       52/Wh 36V - Down Tube Integrated     Downtube - Removable     -       40km to 100km     40km to 100km     40km to 100km     -       4.3* 3 to fhours total charge time     4.4 - 65 hours total charge time     2.4 - 50 ro. Tours total charge time       BROSE Allround     AL 660mm / 31.8mm (Straight)     AL 660mm / 31.8mm (Straight)       AL 30mm - 31.8mm - 0*     go"     AL 660mm / 31.8mm (Straight)       31.8mm (Straight)     AL 660mm / 31.8mm - adjustable 0- 90* with cable Integration     SEROSE 2.2*       27.5*/2*     28*     29*       Alloy Double Wall 30mm (Tubeless Ready)     SHIMANO Bert 1400 CHARK Hydraulic MERO

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.