

**C800 Trekking**

£ 2,149

**B400 Urban Low Step**

£ 0

**M700 ATB Wild**

£ 2,149

**S950 Full Suspension Carbon**

£ 4,799

PRODUCT INFORMATION

PAINTING	-	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-
FRAME SIZES	-	-	S-M (42) - L/XL (46)	-
MAXIMUM BIKE & RIDER WEIGHT	120 Kg	150kg	135Kg	135kg
WEIGHT	Approx. 28 Kg	Approx. 21 Kg	Approx. 27Kg	Approx. 26 Kg
COLOUR(s)	-	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish	-

FRAME

FRAME	28" TREKKING FRAME	28" Aluminium Low Step Frame	MTB Hardtail Aluminum	Full Carbon FS Frame 140mm
SUSPENSION	-	-	Rockshox 35S Travel 120mm Axel Boost 110mm 27.5"/29"	Rockshox Pike Select 29" Travel 140mm Axel Boost 110mm
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS	FSA HS 1.5" to 1-1/8" Tapered SHIS
REAR SHOCK	-	-	-	ROCKSHOX Deluxe Select+ Trunnion 55mm
FORK	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm	Alloy Fork 28"	-	-

DRIVETRAIN & BRAKES

BRAKES	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm	ALHONGA Hydraulic Disc HJ-HT474	SHIMANO Hydraulic MT400	MAGURA Hydraulic MT5
BRAKE ROTOR - Front	-	-	SHIMANO SM-RT30 203mm	MAGURA MDR-C 203mm
BRAKE ROTOR - Rear	-	-	SHIMANO SM-RT30 180mm	MAGURA MDR-C 203mm
SHIFTERS	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS	SHIMANO Altus SL-M2010	SRAM NX 11S	-
REAR DERRAILEUR	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS	SHIMANO Altus RD-M2000 9S	SRAM NX 1x11 Speed	SRAM NX EAGLE 1x12
CASSETTE	SHIMANO DEORE CS-HG500-10 10-SPEED	SHIMANO CS-HG201 9S	SRAM Power Glid 1130 11-42	-
CHAINRING	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T
CRANK	MESSINGSCHLAGER SAMOX Shape 175/0	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0
CHAIN/BELT DRIVE	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE	SHIMANO CN-HG53	KMC E11 Turbo e-bike series	SRAM SX EAGLE 12S
BRAKE ROTOR	SHIMANO SM-RT10 180mm	ALHONGA HJ-DXR1806 180MM	-	-

E-BIKE SYSTEM

DRIVE UNIT	BROSE DRIVE S 90Nm	BAFANG H400B 45Nm; Rear Wheel Motor	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S MAG Horizontal 90Nm
BATTERY	504 Wh 36V - Integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable	522Wh 36V - Integrated on Downtube - Removable	BROSE 630Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	No	Yes	Yes
CHARGER	4A charger - 4 hours total charge time	2A - 5 hours total charge time	4A - 3,6 hours total charge time	4A - 4 hours total charge time
DISPLAY	Brose Display Allround	BAFANG LCD Display DPC11	Brose Display Allround	BROSE Display Remote

WHEELSET

TYRES	CONTINENTAL Tire 29x2,00 Double Fighter III	CONTINENTAL Tire 28x2,00 Contact Cruiser	MAXXIS Rekon S - 27,5x2,6 / M - L/XL- 29x2,4 Black 60 TPI	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding
WHEEL SIZE	29X2,00	28x2,00	27,5" (S) / 29" (M-L/XL)	Mullet: 27,5 / 29
RIMS	ALLOY DOUBLE WALL RIM 36 HOLES	Alloy double wall rim	Alloy Double Wall Rim 30mm	Alloy Double Wall Rim Front: 30/ Rear: 35
SPOKES	BLACK STEEL SPOKES	Stainless steel	Stainless Steel Black	Stainless Steel Black
FRONT HUB	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD	Alloy quick release M9x100	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	-
REAR HUB	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD	BAFANG H400B	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	-

COCKPIT

HANDLEBAR	ALLOY Black	SATORI Alloy Black Ø31.8mm - 660mm	FSA V-Drive Flat 740mm / 31.8mm	FSA Grid Low Riser 800mm/ 35mm
STEM	Steam Ahead	SATORI Ahead Adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°	FSA Grid 50mm/ 35mm / ±6°
GRIPS	Grip GA30 BLACK - MTB 128/128	HERRMANS DD36 Ergonomic	ERGON Grip GA30 Black - MTB	ERGON Grip GA30 Black - MTB

SAFETY & ACCESSORIES

REAR LIGHT	-	-	YES	-
RACK	-	-	YES	-
FRONT LIGHT	AXA Blueline 30 with reflector	AXA Ecoline 15 with reflector	YES	LITEMOVE SE-110 with reflector 110 Lux
MUDGUARD	-	-	YES	-
KICKSTAND	-	-	YES	-
BOTTLE CAGE	-	-	Not Supplied. Frame prepared for standard.	-