









A4cm) - L (48cm) rox. 25kg (g der Painting Scratch Resistant Matte or Glossy Varnish te Star with glossy varnish  Happy with matte finish   Black Suit with te finish ninium Low Step d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Mh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36 TINENTAL Ride Cruiser 28"x2,0"	S (42cm) - M (46cm) - L (50cm) Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish   Moon Grey Gloss with glossy finish Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	S (46cm) - M (52cm) - L (56cm) Approx. 24kg 145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish   Desert Sand with matte finish   Desert Aluminium Low Step - Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- g0° HERRMANS DD36 Ergonomic	- Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
rox. 25kg 49 49 49 49 49 40 40 40 40 40 40 40 40 40 40	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Approx. 24kg 145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish   Desert Sand with matte finish   Desert Sand with matte finish Aluminium Low Step - Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Approx. 26Kg 135Kg Powder Painting Scratch Resistant with Matte Varnish - MTB Hardtail Aluminium Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
rox. 25kg 49 49 49 49 49 40 40 40 40 40 40 40 40 40 40	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Approx. 24kg 145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish   Desert Sand with matte finish   Desert Sand with matte finish Aluminium Low Step - Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Approx. 26Kg 135Kg Powder Painting Scratch Resistant with Matte Varnish - MTB Hardtail Aluminium Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
g der Painting Scratch Resistant Matte or Glossy Varnish te Star with glossy varnish  Happy with matte finish   Black Suit with te finish ninium Low Step d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS dANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish   Desert Sand with matte finish Aluminium Low Step - Rigid Alloy 28° SHIS 1-1/8° BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	135Kg Powder Painting Scratch Resistant with Matte Varnish - MTB Hardtail Aluminium Rockshox 355 Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
der Painting Scratch Resistant Matte or Glossy Varnish te Star with glossy varnish  Happy with matte finish   Black Suit with te finish ninium Low Step d Alloy 28" is 1.5" to 1-1/8" Tapered SHIS dANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish   Desert Sand with matte finish Aluminium Low Step - Rigid Alloy 28° SHIS 1-1/8° BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Powder Painting Scratch Resistant with Matte Varnish - MTB Hardtail Aluminium Rockshox 355 Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
te Star with glossy varnish  Happy with matte finish   Black Suit with te finish ninium Low Step d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Mh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Black Fog with matte minish   Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround - FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Moon Grey with matte finish   Desert Sand with matte finish Aluminium Low Step - Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	- MTB Hardtail Aluminium Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
with matte finish   Black Suit with te finish ninium Low Step d Alloy 28" is 1.5" to 1-1/8" Tapered SHIS dANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Sand with matte finish Aluminium Low Step - Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Mh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround - FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Rigid Alloy 28° SHIS 1-1/8° BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Mh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround - FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Rigid Alloy 28° SHIS 1-1/8° BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
d Alloy 28" s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Mh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	Rigid Alloy 28° SHIS 1-1/8° BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Boost 110mm 27.5"/29" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	- FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	- FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
s 1.5" to 1-1/8" Tapered SHIS MANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
MANO STEPS E5000 40Nm Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
Wh 36V - Semi-integrated in ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	522Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
ntube - Removable m to 100km 6 hours total charge time 4ANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	- Non Removable 40km to 100km - 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	- Removable 40km to 100km Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
6 hours total charge time MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	- 2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Yes 4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	2A - 5 hours total charge time BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	4A - 3,6 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
MANO SC-E6100 60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	BAFANG DP.C11 AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
60mm / 31.8mm (Curved) 0mm - 31.8mm - adjustable 0- RMANS DD36	FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
0mm - 31.8mm - adjustable 0- RMANS DD36	(Straight) FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	AL 90mm - 31.8mm - adjustable 0- 90°	(Straight) FSA V-Drive 60mm/ 31.8mm / ±6°
RMANS DD36	FSA V-Drive 60mm/ 31.8mm / ±6° ERGON GA30	90°	FSA V-Drive 60mm/ 31.8mm / ±6°
	ERGON GA30		· · · · ·
		HERRMANS DD36 Ergonomic	EDOON 0400
TINENTAL Ride Cruiser 28''x2,0''			ERGON GA30
TINENTAL Ride Cruiser 28''x2,0''			
	CONTINENTAL Mountain King 27,5"x2,6"	CONTINENTAL Contact Cruiser 28''x2,0''	MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4"
	27,5"	28''	27,5" (S) / 29" (M-L/XL)
/ Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)
k Stainless Steel	Black Stainless Steel	Stainless Steel	Black Stainless Steel
MANO HB-MT400 100 Thru-axle Im	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-TX506 9x100mm QR	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
4ANO FH-TX505 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	BAFANG H400B 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm
AND Hydraulic MT200	SHIMANO Hydraulic MT200	ALHONGA Hydraulic H I-HT/474	SHIMANO Hydraulic MT400
1		,	SHIMANO SM-RT30 203mm
MANO SM-RT 160mm	SHIMANO SM-RT10 180mm	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT30 180mm
4ANO Altus 9S	SHIMANO Deore 10S	SHIMANO Altus 9S	SRAM NX 11S
ANO Altus 9S 11-36T	SHIMANO Deore 10S 11-42T	SHIMANO Altus 9S 11-36T	SRAM Power Glid 1130 11-42
MANO Altus 9S	SHIMANO Deore 10S	SHIMANO Altus 9S	SRAM NX 11S
MANO SN-CRE50 38T	SAMOX BCD 104 36T	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T
4ANO FC-E5010 - 175	SAMOX Shape 175/5	MIRANDA JIS 170	SAMOX Shape 170/0
MANO CN-HG53	SHIMANO CN-E6090	SHIMANO CN-HG53	KMC E11 Turbo e-bike series
SKS	Yes - HSA	Yes - SKS	Yes - FSA
ANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO City AVS (max.: 25Kg)	-
Blueline 30 with reflector	AXA Blueline 30 with reflector	AXA Ecoline 15 with reflector	-
ADILLY with reflector	AXA Slim with reflector	AXA Slim with reflector	-
ANVELO Dux			-
			-
included Frame not propared			- Not included. Sold separately.
			SELLE SAN MARCO X3 e-bike
			FSA Gossamer 31.6mm / 350mm
lack 350mm 30,9mm/15mm	/20mm	AL Black 300mm 31,6mm/15mm	/20mm
		,	Alloy black with screw
	LINER SPEZIAL LIST WITH reflectors	NECU WILL (PERCIONS	UNION SP-400 Flat with reflectors
иг и. и. и. и. и. и. и. и. и. и. и. и. и.	n ANO FH-TX505 135mm ANO FH-TX505 135mm ANO SM-RT 180mm ANO SM-RT 180mm ANO SM-RT 160mm ANO Altus 9S ANO Altus 9S ANO Altus 9S ANO Altus 9S ANO SN-CRE50 38T ANO FC-E5010 - 175 ANO CN-H653 SKS NVELO Tour AVS (max.: 25Kg) Blueline 30 with reflector ADILLY with reflector NVELO Dux cluded. Frame not prepared. E ROYAL Rio Gel ack 350mm 30,9mm/15mm black with quick release	n Thru-axle 15mm ANO FH-TX505 135mm SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm ANO Hydraulic MT200 SHIMANO Hydraulic MT200 ANO SM-RT 180mm SHIMANO SM-RT10 180mm ANO SM-RT 160mm SHIMANO SM-RT10 180mm ANO Altus 9S SHIMANO Deore 10S ANO N-CRE50 38T SAM0X Shape 175/5 ANO CN-H653 SHIMANO CN-E6090 SKS Yes - FSA NVELO Tour AVS (max.: 25Kg) ATRANVELO Tour AVS (max.: 25Kg) NVELO Tour AVS (max.: 25Kg) ATRANVELO Tour AVS (max.: 25Kg) NVELO Dux ATRANVELO Dux SKS	nThru-axle 15mmSHIMANO HB-1X506 9X100mm 0RAN0 FH-TX505 135mmSHIMANO HB-MT400-B Boost 148 Thru-axle 12mmBAFANG H400B 135mmAN0 Hydraulic MT200SHIMANO Hydraulic MT200ALHONGA Hydraulic HJ-HT474AN0 SM-RT 180mmSHIMANO SM-RT10 180mmALHONGA HJ-DXR1806 180MMAN0 SM-RT 160mmSHIMANO SM-RT10 180mmALHONGA HJ-DXR1806 180MMAN0 Altus 9SSHIMANO Deore 10SSHIMANO Altus 9SAN0 Altus 9SSHIMANO Deore 10SSHIMANO Altus 9SANO Altus 9SSHIMANO Deore 10SSHIMANO Altus 9SANO CN-E50 38TSAMOX Shape 175/5MIRANDA Lis 170AN0 CN-HG53SHIMANO CN-E6090SHIMANO CN-HG53SKSYes - FSAYes - SKSVELO Tour AVS (max:: 25Kg)ATRANVELO Tour AVS (max:: 25Kg)ATRANVELO Tour AVS (max:: 25Kg)ATRANVELO City AVS (max:: 25Kg)Alueline 30 with reflectorAXA Blueline 30 with reflectorADILLY with reflectorAXA Blueline 30 with reflectorAVA Slim with reflectorAXA Slim with reflectorNVELO DuxTRANVELO DuxATRANVELO DuxSKSSKSSkSncluded. Frame not prepared.Not included. Sold separately.E ROYAL Rio GelSELLE ROYAL ShadowSELLE ROYAL Rio GelAck 350mm 30,9mm/15mmFSA Gossamer 350mm 31.6mmAL Black 300mm 31.6mm/15mm </td

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.