

**B400 Urban Low Step**

£ 0

**M700 ATB Wild**

£ 2,149

**S950 Full Suspension Carbon**

£ 4,799

**C800 Trekking**

£ 2,149

PRODUCT INFORMATION

PAINTING	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-	-
FRAME SIZES	-	S-M (42) - L/XL (46)	-	-
MAXIMUM BIKE & RIDER WEIGHT	150kg	135Kg	135kg	120 Kg
WEIGHT	Approx. 21 Kg	Approx. 27Kg	Approx. 26 Kg	Approx. 28 Kg
COLOUR(s)	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish	-	-

FRAME

FRAME	28" Aluminium Low Step Frame	MTB Hardtail Aluminum	Full Carbon FS Frame 140mm	28" TREKKING FRAME
SUSPENSION	-	Rockshox 35S Travel 120mm Axel Boost 110mm 27.5"/29"	Rockshox Pike Select 29" Travel 140mm Axel Boost 110mm	-
HEADSET	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS	FSA HS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS
REAR SHOCK	-	-	ROCKSHOX Deluxe Select+ Trunnion 55mm	-
FORK	Alloy Fork 28"	-	-	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm

DRIVETRAIN & BRAKES

BRAKES	ALHONGA Hydraulic Disc HJ-HT474	SHIMANO Hydraulic MT400	MAGURA Hydraulic MT5	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm
BRAKE ROTOR - Front	-	SHIMANO SM-RT30 203mm	MAGURA MDR-C 203mm	-
BRAKE ROTOR - Rear	-	SHIMANO SM-RT30 180mm	MAGURA MDR-C 203mm	-
SHIFTERS	SHIMANO Altus SL-M2010	SRAM NX 11S	-	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS
REAR DERRAILEUR	SHIMANO Altus RD-M2000 9S	SRAM NX 1x11 Speed	SRAM NX EAGLE 1x12	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS
CASSETTE	SHIMANO CS-HG201 9S	SRAM Power Glid 1130 11-42	-	SHIMANO DEORE CS-HG500-10 10-SPEED
CHAINRING	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T
CRANK	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0
CHAIN/BELT DRIVE	SHIMANO CN-HG53	KMC E11 Turbo e-bike series	SRAM SX EAGLE 12S	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE
BRAKE ROTOR	ALHONGA HJ-DXR1806 180MM	-	-	SHIMANO SM-RT10 180mm

E-BIKE SYSTEM

DRIVE UNIT	BAFANG H400B 45Nm; Rear Wheel Motor	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S 90Nm
BATTERY	360Wh 36V - Integrated on Downtube - Non Removable	522Wh 36V - Integrated on Downtube - Removable	BROSE 630Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	No	Yes	Yes	Yes
CHARGER	2A - 5 hours total charge time	4A - 3,6 hours total charge time	4A - 4 hours total charge time	4A charger - 4 hours total charge time
DISPLAY	BAFANG LCD Display DPC11	Brose Display Allround	BROSE Display Remote	Brose Display Allround

WHEELSET

TYRES	CONTINENTAL Tire 28x2,00 Contact Cruiser	MAXXIS Rekon S - 27,5x2,6 / M - L/XL- 29x2,4 Black 60 TPI	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	CONTINENTAL Tire 29x2,00 Double Fighter III
WHEEL SIZE	28x2,00	27,5" (S) / 29" (M-L/XL)	Mullet: 27,5 / 29	29x2,00
RIMS	Alloy double wall rim	Alloy Double Wall Rim 30mm	Alloy Double Wall Rim Front: 30/ Rear: 35	ALLOY DOUBLE WALL RIM 36 HOLES
SPOKES	Stainless steel	Stainless Steel Black	Stainless Steel Black	BLACK STEEL SPOKES
FRONT HUB	Alloy quick release M9x100	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	-	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD
REAR HUB	BAFANG H400B	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	-	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD

COCKPIT

HANDLEBAR	SATORI Alloy Black Ø31.8mm - 660mm	FSA V-Drive Flat 740mm / 31.8mm	FSA Grid Low Riser 800mm/ 35mm	ALLOY BLACK
STEM	SATORI Ahead Adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°	FSA Grid 50mm/ 35mm / ±6°	Steam Ahead
GRIPS	HERRMANS DD36 Ergonomic	ERGON Grip GA30 Black - MTB	ERGON Grip GA30 Black - MTB	Grip GA30 BLACK - MTB 128/128

SAFETY & ACCESSORIES

REAR LIGHT	-	YES	-	-
RACK	-	YES	-	-
FRONT LIGHT	AXA Ecoline 15 with reflector	YES	LITEMOVE SE-110 with reflector 110 Lux	AXA Blueline 30 with reflector
MUDGUARD	-	YES	-	-
KICKSTAND	-	YES	-	-
BOTTLE CAGE	-	Not Supplied. Frame prepared for standard.	-	-