



**E850 Urban Motion**  
£ 2,399



**B400 Urban High Step**  
£ 1,599



**B400 Urban Low Step**  
£ 0



**M500 ATB Wild**  
£ 2,349

## PRODUCT INFORMATION

MAXIMUM BIKE & RIDER WEIGHT	145kg	150kg	150kg	120 Kg
WEIGHT	26,5kg	Approx. 24 Kg	Approx. 21 Kg	Approx. 26 Kg

## FRAME

FRAME	28" Aluminium 6061 Low Step Frame	28" Aluminium High Setp Frame	28" Aluminium Low Step Frame	27,5" MTB HARDTAIL - 6061 Hydroformed Aluminum
SUSPENSION	-	-	-	SrSuntour RAIDON34 LOR DS Travel 130mm Axel Bost 110mm 27,5"
HEADSET	Acros Cable Integration AZX 585 with IPS / ICR / Block Lock 150°	Semi integrated 1-1/8"	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS
FORK	Rigid Alloy Fork 28" with Integrated Cable	Rigid Alloy 28"	Alloy Fork 28"	-

## DRIVETRAIN & BRAKES

BRAKES	SHIMANO Hydraulic MT200	ALHONGA Hydraulic Disc HJ-HT474	ALHONGA Hydraulic Disc HJ-HT474	Shimano Hydraulic MT200
SHIFTERS	SHIMANO Nexus 8	SHIMANO Altus SL-M2010	SHIMANO Altus SL-M2010	SHIMANO DEORE SL-M6000-R 10 Speed
REAR DERRAILEUR	No	SHIMANO Altus RD-M2000 9S	SHIMANO Altus RD-M2000 9S	SHIMANO DEORE 1x10 Speed
CASSETTE	No	SHIMANO CS-HG201- 9S	SHIMANO CS-HG201 9S	SHIMANO DEORE 10 Speed
CHAINRING	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow BCD104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T
CRANK	SHIMANO FC-E6100 175mm	MIRANDA PSI 170/12	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/5
CHAIN/BELT DRIVE	Chain: SHIMANO NX10	SHIMANO CN-HG53	SHIMANO CN-HG53	SHIMANO CN-E6090 10-Speed E-Bike 113 Chain Links
BRAKE ROTOR	SHIMANO SM-RT10 180mm	ALHONGA HJ-DXR1806 180MM	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT10 180mm
FRONT DERRAILEUR	-	-	-	Non applicable

## E-BIKE SYSTEM

DRIVE UNIT	SHIMANO Steps E6100 60Nm	BAFANG H400B 45N - Rear wheel	BAFANG H400B 45Nm; Rear Wheel Motor	BROSE DRIVE S 90Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable	360Wh 36V - Integrated on Downtube - Non Removable	Snake Battery - 504 Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	No	No	Yes
CHARGER	2A Charger - 7 hours total charge time	2A - 5 hours total charge time	2A - 5 hours total charge time	2A charger - 7 hours total charge time
DISPLAY	SHIMANO SC-E6100	BAFANG LCD Display DP.C11	BAFANG LCD Display DP.C11	Brose Display Allround

## WHEELSET

TYRES	28 x 2,2	CONTINENTAL Tire 29x2,00 Double Fighter III	CONTINENTAL Tire 28x2,00 Contact Cruiser	CONTINENTAL TYRES MOUNTAIN KING 27,5x2,6"
WHEEL SIZE	28"	29x2,00	28x2,00	27,5x2,6
RIMS	Alloy Double Wall Rim 25	Alloy double wall rim	Alloy double wall rim	Double wall aluminium rims
SPOKES	Stainless Steel Black	Stainless stell	Stainless steel	Stainless Steel Black
FRONT HUB	SHIMANO HB-MT400	Alloy quick release M9x100	Alloy quick release M9x100	SHIMANO HB-MT400-B
REAR HUB	SHIMANO Nexus SG-C6001-8D	BAFANG H400B	BAFANG H400B	SHIMANO FH-M6010-B DEORE

## COCKPIT

HANDLEBAR	Alloy Black Curved 31,8 660mm	SATORI alloy black	SATORI Alloy Black Ø31,8mm - 660mm	FSA V-Drive Flat 740mm / 31,8mm
STEM	Adjustable 90mm with Cable Integration	AHEAD alloy black	SATORI Ahead Adjustable 0-90°	FSA V-Drive 60mm/ 31,8mm / ±6°
GRIPS	Grip GP1-L Nexus/Rohloff 128/93	HERRMANS DD36 Ergonomic	HERRMANS DD36 Ergonomic	ERGON GA30 BLACK - MTB 128/128

## SAFETY & ACCESSORIES

FRONT LIGHT	SPANNINGA Axendo 40 with reflector	AXA Ecoline 15 with reflector	AXA Ecoline 15 with reflector	Yes
SEAT POST	Alloy Black	ZOOM Alloy Black Ø31,6mm x 300mm	ZOOM Alloy Black Ø31,6mm x 300mm	FSA ALLOY
SEAT CLAMP	Seatclamp alloy black with quick release	Alloy black with screw 34,9mm	Alloy black with screw 34,9mm	Seatclamp alloy black with screw
SADDLE	SELLE ROYAL Rio Gel	SELLE ROYAL ESSENZA	SELLE ROYAL RIO Gel	SELLE ROYAL Shadow GEL with Black Guards
PEDALS	UNION non-slip with reflector	NECO with reflectors	NECO with reflectors	Union Ball RingCity with Retro Reflectors
FRAMELOCK	Yes - AXA Block XXL	Not suplied. Frame prepared	Not suplied. Frame prepared	-

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.