

**E850 Urban Motion**

£ 2,399

**S950 Full Suspension Carbon**

£ 4,799

**C800 Trekking**

£ 2,149

**M700 ATB Wild**

£ 2,149

PRODUCT INFORMATION

PAINTING	-	-	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish
FRAME SIZES	-	-	-	S-M (42) - L/XL (46)
MAXIMUM BIKE & RIDER WEIGHT	145kg	135kg	120 Kg	135Kg
WEIGHT	26,5kg	Approx. 26 Kg	Approx. 28 Kg	Approx. 27Kg
COLOUR(s)	-	-	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish

FRAME

FRAME	28" Aluminium 6061 Low Step Frame	Full Carbon FS Frame 140mm	28" TREKKING FRAME	MTB Hardtail Aluminum
SUSPENSION	-	Rockshox Pike Select 29" Travel 140mm Axel Boost 110mm	-	Rockshox 35S Travel 120mm Axel Boost 110mm 27,5"/29"
HEADSET	Acros Cable Integration AZX 585 with IPS / ICR / Block Lock 150°	FSA HS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS
REAR SHOCK	-	ROCKSHOX Deluxe Select+ Trunnium 55mm	-	-
FORK	Rigid Alloy Fork 28" with Integrated Cable	-	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm	-

DRIVETRAIN & BRAKES

BRAKES	SHIMANO Hydraulic MT200	MAGURA Hydraulic MT5	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm	SHIMANO Hydraulic MT400
BRAKE ROTOR - Front	-	MAGURA MDR-C 203mm	-	SHIMANO SM-RT30 203mm
BRAKE ROTOR - Rear	-	MAGURA MDR-C 203mm	-	SHIMANO SM-RT30 180mm
SHIFTERS	SHIMANO Nexus 8	-	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS	SRAM NX 11S
REAR DERRAILEUR	No	SRAM NX EAGLE 1x12	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS	SRAM NX 1x11 Speed
CASSETTE	No	-	SHIMANO DEORE CS-HG500-10 10-SPEED	SRAM Power Glid 1130 11-42
CHAINRING	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow 3D BCD104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T	MIRANDA ChainFlow 3D BCD104 38T
CRANK	SHIMANO FC-E6100 175mm	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0
CHAIN/BELT DRIVE	Chain: SHIMANO NX10	SRAM SX EAGLE 12S	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE	KMC E11 Turbo e-bike series
BRAKE ROTOR	SHIMANO SM-RT10 180mm	-	SHIMANO SM-RT10 180mm	-

E-BIKE SYSTEM

DRIVE UNIT	SHIMANO Steps E6100 60Nm	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S 90Nm	BROSE DRIVE S MAG Horizontal 90Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	BROSE 630Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	Yes	Yes	Yes
CHARGER	2A Charger - 7 hours total charge time	4A - 4 hours total charge time	4A charger - 4 hours total charge time	4A - 3,6 hours total charge time
DISPLAY	SHIMANO SC-E6100	BROSE Display Remote	Brose Display Allround	Brose Display Allround

WHEELSET

TYRES	28 x 2,2	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	CONTINENTAL Tire 29x2,00 Double Fighter III	MAXXIS Rekon S - 27,5x2,6 / M - L/XL-29x2,4 Black 60 TPI
WHEEL SIZE	28"	Mullet: 27,5 / 29	29X2,00	27,5" (S) / 29" (M-L/XL)
RIMS	Alloy Double Wall Rim 25	Alloy Double Wall Rim Front: 30/ Rear: 35	ALLOY DOUBLE WALL RIM 36 HOLES	Alloy Double Wall Rim 30mm
SPOKES	Stainless Steel Black	Stainless Steel Black	BLACK STEEL SPOKES	Stainless Steel Black
FRONT HUB	SHIMANO HB-MT400	-	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
REAR HUB	SHIMANO Nexus SG-C6001-8D	-	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm

COCKPIT

HANDLEBAR	Alloy Black Curved 31,8 660mm	FSA Grid Low Riser 800mm/ 35mm	ALLOY Black	FSA V-Drive Flat 740mm / 31.8mm
STEM	Adjustable 90mm with Cable Integration	FSA Grid 50mm/ 35mm / ±6°	Steam Ahead	FSA V-Drive 60mm/ 31.8mm / ±6°
GRIPS	Grip GP1-L Nexus/Rohloff 128/93	ERGON Grip GA30 Black - MTB	Grip GA30 BLACK - MTB 128/128	ERGON Grip GA30 Black - MTB

SAFETY & ACCESSORIES

REAR LIGHT	-	-	-	YES
RACK	-	-	-	YES
FRONT LIGHT	SPANNINGA Axendo 40 with reflector	LITEMOVE SE-110 with reflector 110 Lux	AXA BlueLine 30 with reflector	YES
MUDGUARD	-	-	-	YES
KICKSTAND	-	-	-	YES
BOTTLE CAGE	-	-	-	Not Suplied. Frame prepared for standard.