



C800 Urban Motion £ 2,149





/arnish with Matte minish Moon finish Moon finish Moon at Travel n 27,5" - Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR FSA 1.5" to 10Nm BROSE DR 504Wh 36 Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI ' 31.8mm AL 660mm 90° ERGOTECH	kg inting Scratch Resistant or Glossy Varnish with matte finish n Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time	M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30 CONTINENTAL Double Fighter III	
Approx. 22 120kg 120k	kg inting Scratch Resistant or Glossy Varnish with matte finish a Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time DT Display a / 31.8mm (Curved) - 31.8mm - adjustable 0- IEG-AMBITION	Approx. 27kg 120kg - White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Approx. 28kg 190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish J Dark Olive with matte finish J Emerald Green with glossy varnish C Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS C BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karsight) FSA V-Drive 740mm / 31.8mm (Straight)
Approx. 22 120kg 120k	kg inting Scratch Resistant or Glossy Varnish with matte finish a Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time DT Display a / 31.8mm (Curved) - 31.8mm - adjustable 0- IEG-AMBITION	Approx. 27kg 120kg - White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Approx. 28kg 190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish J Dark Olive with matte finish J Emerald Green with glossy varnish C Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS C BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karsight) FSA V-Drive 740mm / 31.8mm (Straight)
120kg tch Resistant Powder Pa /arnish with Matte minish Moon Black Suit /finish Black Suit Jtail Aluminium . Air Travel - n 27,5" - Rigid Alloy - 0Nm BROSE DR /h 36V - 504Wh 36 .be - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI - '31.8mm AL 660mm 81.8mm / ±6° AL 90mm go% ERGOTECF	inting Scratch Resistant or Glossy Varnish with matte finish n Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time DT Display n / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	120kg 120kg White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish Dark Olive with matte finish Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)
tch Resistant Powder Pa with Matter minish Moon finish Moon finish Moon at Travel n 27,5" - Rigid Alloy ered SHIS FSA 1.5" to NMM BROSE DR fN 36V - 504Wh 36 Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI ' 31.8mm AL 660mm 90° ERGOTECH	e or Glossy Varnish with matte finish a Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time DT Display a / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	- White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish Dark Olive with matte finish Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5'' to 1-1/8'' Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround KL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)
/arnish with Matte minish Moon finish Moon finish Moon at Travel n 27,5" - Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR FSA 1.5" to 10Nm BROSE DR 504Wh 36 Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI ' 31.8mm AL 660mm 90° ERGOTECH	e or Glossy Varnish with matte finish a Low Step 28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable 20km hours total charge time DT Display a / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	with Matte or Glossy Varnish Hock Grey with matte finish Dark Olive with matte finish Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karaight) FSA V-Drive 740mm / 31.8mm (Straight)
rfinish Black Sult dtail Aluminium Air Travel n 27,5'' - Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR Alloy 10Nm BROSE DR 504Wh 36 Wh 36V - 504Wh 36 Wh 36V - 504Wh 36 Wh 36V - 504Wh 36 Wh 36V - 2000 1000 - 2000	28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Olive with matte finish Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karsight) FSA V-Drive 740mm / 31.8mm (Straight)
Air Travel n 27,5" Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm 400000000000000000000000000000000000	28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	 Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30 	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karson Allround Karsight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm /
Air Travel n 27,5" Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm 400000000000000000000000000000000000	28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	 Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30 	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karson Allround Karsight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm /
Air Travel n 27,5'' Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm BROSE DR 10Nm 400000000000000000000000000000000000	28" 1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	 Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30 	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karson Allround Karsight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm / Straight) FSA V-Drive 740mm /
Rigid Alloy ered SHIS FSA 1.5" to 10Nm BROSE DR /h 36V - 504Wh 36 ube - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI 31.8mm AL 660mn 90° ERGOTECH	1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	- SA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround KL780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)
ered SHIS FSA 1.5" to IONM BROSE DR IONM BROSE DR SO4Wh 36 100 - 504Wh 36 100 - 704Wh 36	1-1/8" Tapered SHIS VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)
IONM BROSE DR I/h 36V - 504Wh 36 ibe - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI ' 31.8mm AL 660mm 90° ERGOTECH ain King	VE C Horizontal 50Nm V - Semi-Integrated on - Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)
/h 36V - 504Wh 36 ibe - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI '31.8mm AL 660mm 90° ERGOTECH	V - Semi-Integrated on - Removable JOkm hours total charge time DT Display n / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
/h 36V - 504Wh 36 ibe - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI '31.8mm AL 660mm 90° ERGOTECH	V - Semi-Integrated on - Removable JOkm hours total charge time DT Display n / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
ibe - Removable Downtube 40km to 10 Yes rge time 4A - 4 to 5 MARQUARI '31.8mm AL 660mm 90° ERGOTECH	- Removable D0km hours total charge time DT Display n/ 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
Yes rge time 4A - 4 to 5 MARQUARI '31.8mm AL 660mm \$1.8mm / ±6° AL 90mm 90° ERGOTECH	hours total charge time DT Display n / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
rge time 4A - 4 to 5 MARQUARI '31.8mm AL 660mn 31.8mm / ±6° AL 90mm 90° ERGOTECH	DT Display	4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
MARQUARI '31.8mm AL 660mm 31.8mm / ±6° AL 90mm 90° ERGOTECH	DT Display	BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
' 31.8mm AL 660mm 31.8mm / ±6° AL 90mm 90° ERGOTECH	n / 31.8mm (Curved) - 31.8mm - adjustable 0- I EG-AMBITION	AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	AL 780mm / 318mm / Rise 20mm (Straight) FSA V-Drive 740mm / 318mm (Straight) AL 50mm - 318mm - 0°
AL 90mm 31.8mm / ±6° AL 90mm 90° ERGOTECH	- 31.8mm - adjustable 0- I EG-AMBITION	AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	(Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
AL 90mm 31.8mm / ±6° AL 90mm 90° ERGOTECH	- 31.8mm - adjustable 0- I EG-AMBITION	AL 90mm - 31.8mm - adjustable 0- 90° ERGON GA30	(Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°
ein King	EG-AMBITION	90° ERGON GA30	
ain King			ERGON GA30
ain King CONTINEN	TAL Ride Cruiser 28''x2 2''	CONTINENTAL Double Fighter III	
ain King CONTINEN	TAL Ride Cruiser 28''x2 2''	CONTINENTAL Double Fighter III	
CONTINEN	TAL Ride Cruiser 28''x2 2''		CONTINENTAL Mountain king
		29"x2,0"	27,5"x2,6" (Tubeless Ready)
28''		29"	27,5"
nm Alloy Doub	le 25mm	Alloy Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)
Black Stair	nless Steel	Black Stainless Steel	Black Stainless Steel
-B Boost 110 SHIMANO 15mm	HB-MT400 100 Thru-axle	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
-B Boost 148 SHIMANO	NEXUS SG-C6001 135mm	SHIMANO Deore M6000 135mm	SHIMANO Deore M6000 135mm
T200 CLARKS H	/draulic M2	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT400
	1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 203mm
	1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 180mm
-		SHIMANO Deore 10S	SHIMANO Deore 11S
11-42T -			SHIMANO Deore 11S 11-51T
	NEXUS 8		SHIMANO Deore 11S
MIRANDA	ChainFlow BCD 104 38T		MIRANDA ChainFlow 3D BCD104 38T
		SAMOX Shape 175/0	SAMOX Shape 170/0
		SHIMANO CN-E6090	KMC E11 Turbo e-bike series
		Yes - FSA	Yes - FSA
(max:25Kg) ATRANVEL	n City AVS (max · 25Kn)	ATRANVELO Tour AVS (max · 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
	1 1 01		SPANNINGA Axendo 40 with reflector
			PICCADILY with reflector
			ATRANVELO Dux
			SKS
		Yes	Yes
SKS Yes	ed. Sold senarately	Not included. Sold separately.	Not included. Sold separately.
SKS Yes	sa. Sola separately.	SELLE ROYAL Essenza Moderate Gel	SELLE ROYAL Essenza Moderate Gel
SKS Yes parately. Not include			
SKS Yes parately. Not include SELLE ROY		AL Black 350mm 31,6mm/15mm	AL Black 350mm 31,6mm/15mm
SKS Yes Darately. Not include SELLE ROY M 31.6mm AL Black 3	AL Rio Gel 50mm 27.2mm/15mm	, .	· · ·
SKS Yes Darately. Not include M SELLE ROY M 31.6mm AL Black 3 M Alloy black	AL Rio Gel	AL Black 350mm 31,6mm/15mm Alloy black with quick release UNION SP-827 Flat with reflectors	AL Black 350mm 31,6mm/15mm Alloy black with quick release UNION SP-827 Flat with reflectors
; r	SHIMANO I MIRANDA I SAMOX Sha SHIMANO I Yes - HEBIE (max.: 25Kg) ATRANVEL reflector AXA Bluelir or PICCADILY ATRANVEL SKS Yes	SHIMANO NEXUS 8 MIRANDA ChainFlow BCD 104 38T SAMOX Shape 175 SHIMANO CN-NX10 Yes - HEBIE (max.: 25Kg) ATRANVELO City AVS (max.: 25Kg) reflector AXA Blueline 30 with reflector or PICCADILY with reflector ATRANVELO Dux SKS	SHIMANO NEXUS 8SHIMANO Deore 10SMIRANDA ChainFlow BCD 104 38TSAMOX BCD 104 36TSAMOX Shape 175SAMOX Shape 175/0SHIMANO CN-NX10SHIMANO CN-E6090Yes - HEBIEYes - FSAG (max.: 25Kg)ATRANVELO City AVS (max.: 25Kg)ATRANVELO City AVS (max.: 25Kg)ATRANVELO Tour AVS (max.: 25Kg)reflectorAXA Blueline 30 with reflectorAXA Blueline 30 with reflectorPICCADILLY with reflectororPICCADILY with reflectorATRANVELO DuxATRANVELO DuxSKSSKSYesYesparately.Not included. Sold separately.wSELLE ROYAL Rio GelSELLE ROYAL Rio GelSELLE ROYAL Essenza Moderate Gel

* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.