



S950 Full Suspension Carbon
£ 4,799



M700 ATB Wild
£ 2,149



C800 Trekking
£ 2,149



E850 Urban Motion
£ 2,399

PRODUCT INFORMATION

PAINTING	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-	-
FRAME SIZES	-	S-M (42) - L/XL (46)	-	-
MAXIMUM BIKE & RIDER WEIGHT	135kg	135Kg	120 Kg	145kg
WEIGHT	Approx. 26 Kg	Approx. 27Kg	Approx. 28 Kg	26,5kg
COLOUR(S)	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish	-	-

FRAME

FRAME	Full Carbon FS Frame 140mm	MTB Hardtail Aluminum	28" TREKKING FRAME	28" Aluminium 6061 Low Step Frame
SUSPENSION	Rockshox Pike Select 29" Travel 140mm Axel Boost 110mm	Rockshox 35S Travel 120mm Axel Boost 110mm 27.5"/29"	-	-
HEADSET	FSA HS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	Acros Cable Integration AZX 585 with IPS / ICR / Block Lock 150°
REAR SHOCK	ROCKSHOX Deluxe Select+ Trunnion 55mm	-	-	-
FORK	-	-	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm	Rigid Alloy Fork 28" with Integrated Cable

DRIVETRAIN & BRAKES

BRAKES	MAGURA Hydraulic MT5	SHIMANO Hydraulic MT400	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm	SHIMANO Hydraulic MT200
BRAKE ROTOR - Front	MAGURA MDR-C 203mm	SHIMANO SM-RT30 203mm	-	-
BRAKE ROTOR - Rear	MAGURA MDR-C 203mm	SHIMANO SM-RT30 180mm	-	-
SHIFTERS	-	SRAM NX 11S	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS	SHIMANO Nexus 8
REAR DERRAILEUR	SRAM NX EAGLE 1x12	SRAM NX 1x11 Speed	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS	No
CASSETTE	-	SRAM Power Glid 1130 11-42	SHIMANO DEORE CS-HG500-10 10-SPEED	No
CHAINRING	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T	SHIMANO SM-CRE61 38T
CRANK	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	SHIMANO FC-E6100 175mm
CHAIN/BELT DRIVE	SRAM SX EAGLE 12S	KMC E11 Turbo e-bike series	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE	Chain: SHIMANO NX10
BRAKE ROTOR	-	-	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm

E-BIKE SYSTEM

DRIVE UNIT	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S 90Nm	SHIMANO Steps E6100 60Nm
BATTERY	BROSE 630Wh 36V - Integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	Yes	Yes	Yes
CHARGER	4A - 4 hours total charge time	4A - 3,6 hours total charge time	4A charger - 4 hours total charge time	2A Charger - 7 hours total charge time
DISPLAY	BROSE Display Remote	Brose Display Allround	Brose Display Allround	SHIMANO SC-E6100

WHEELSET

TYRES	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	MAXXIS Rekon S - 27,5x2,6 / M - L/XL- 29x2,4 Black 60 TPI	CONTINENTAL Tire 29x2,00 Double Fighter III	28 x 2,2
WHEEL SIZE	Mullet: 27,5 / 29	27,5" (S) / 29" (M-L/XL)	29X2,00	28"
RIMS	Alloy Double Wall Rim Front: 30/ Rear: 35	Alloy Double Wall Rim 30mm	ALLOY DOUBLE WALL RIM 36 HOLES	Alloy Double Wall Rim 25
SPOKES	Stainless Steel Black	Stainless Steel Black	BLACK STEEL SPOKES	Stainless Steel Black
FRONT HUB	-	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD	SHIMANO HB-MT400
REAR HUB	-	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD	SHIMANO Nexus SG-C6001-8D

COCKPIT

HANDLEBAR	FSA Grid Low Riser 800mm/ 35mm	FSA V-Drive Flat 740mm / 31.8mm	ALLOY Black	Alloy Black Curved 31,8 660mm
STEM	FSA Grid 50mm/ 35mm / ±6°	FSA V-Drive 60mm/ 31.8mm / ±6°	Steam Ahead	Adjustable 90mm with Cable Integration
GRIPS	ERGON Grip GA30 Black - MTB	ERGON Grip GA30 Black - MTB	Grip GA30 BLACK - MTB 128/128	Grip GP1-L Nexus/Rohloff 128/93

SAFETY & ACCESSORIES

REAR LIGHT	-	YES	-	-
RACK	-	YES	-	-
FRONT LIGHT	LITEMOVE SE-110 with reflector 110 Lux	YES	AXA BlueLine 30 with reflector	SPANNINGA Axendo 40 with reflector
MUDGUARD	-	YES	-	-
KICKSTAND	-	YES	-	-
BOTTLE CAGE	-	Not Suplied. Frame prepared for standard.	-	-