



S950 Full Suspension Carbon
£ 4,799



M700 ATB Wild
£ 2,149



E850 Urban Motion
£ 2,399



C800 Trekking
£ 2,149

PRODUCT INFORMATION

PAINTING	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-	-
FRAME SIZES	-	S-M (42) - L/XL (46)	-	-
MAXIMUM BIKE & RIDER WEIGHT	135kg	135Kg	145kg	120 Kg
WEIGHT	Approx. 26 Kg	Approx. 27Kg	26,5kg	Approx. 28 Kg
COLOUR(s)	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish	-	-

FRAME

FRAME	Full Carbon FS Frame 140mm	MTB Hardtail Aluminum	28" Aluminium 6061 Low Step Frame	28" TREKKING FRAME
SUSPENSION	Rockshox Pike Select 29" Travel 140mm Axle Boost 110mm	Rockshox 35S Travel 120mm Axel Boost 110mm 27.5"/29"	-	-
HEADSET	FSA HS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	Acros Cable Integration AZX 585 with IPS / ICR / Block Lock 150°	FSA 1.5" to 1-1/8" Tapered SHIS
REAR SHOCK	ROCKSHOX Deluxe Select+ Trunnion 55mm	-	-	-
FORK	-	-	Rigid Alloy Fork 28" with Integrated Cable	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm

DRIVETRAIN & BRAKES

BRAKES	MAGURA Hydraulic MT5	SHIMANO Hydraulic MT400	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm
BRAKE ROTOR - Front	MAGURA MDR-C 203mm	SHIMANO SM-RT30 203mm	-	-
BRAKE ROTOR - Rear	MAGURA MDR-C 203mm	SHIMANO SM-RT30 180mm	-	-
SHIFTERS	-	SRAM NX 11S	SHIMANO Nexus 8	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS
REAR DERRAILEUR	SRAM NX EAGLE 1x12	SRAM NX 1x11 Speed	No	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS
CASSETTE	-	SRAM Power Glid 1130 11-42	No	SHIMANO DEORE CS-HG500-10 10-SPEED
CHAINRING	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow 3D BCD104 38T	SHIMANO SM-CRE61 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T
CRANK	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	SHIMANO FC-E6100 175mm	MESSINGSCHLAGER SAMOX Shape 175/0
CHAIN/BELT DRIVE	SRAM SX EAGLE 12S	KMC E11 Turbo e-bike series	Chain: SHIMANO NX10	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE
BRAKE ROTOR	-	-	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm

E-BIKE SYSTEM

DRIVE UNIT	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S MAG Horizontal 90Nm	SHIMANO Steps E6100 60Nm	BROSE DRIVE S 90Nm
BATTERY	BROSE 630Wh 36V - Integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	Yes	Yes	Yes
CHARGER	4A - 4 hours total charge time	4A - 3,6 hours total charge time	2A Charger - 7 hours total charge time	4A charger - 4 hours total charge time
DISPLAY	BROSE Display Remote	Brose Display Allround	SHIMANO SC-E6100	Brose Display Allround

WHEELSET

TYRES	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	MAXXIS Rekon S - 27,5x2,6 / M - L/XL- 29x2,4 Black 60 TPI	28 x 2,2	CONTINENTAL Tire 29x2,00 Double Fighter III
WHEEL SIZE	Mullet: 27,5 / 29	27,5" (S) / 29" (M-L/XL)	28"	29X2,00
RIMS	Alloy Double Wall Rim Front: 30/ Rear: 35	Alloy Double Wall Rim 30mm	Alloy Double Wall Rim 25	ALLOY DOUBLE WALL RIM 36 HOLES
SPOKES	Stainless Steel Black	Stainless Steel Black	Stainless Steel Black	BLACK STEEL SPOKES
FRONT HUB	-	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD
REAR HUB	-	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO Nexus SG-C6001-8D	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD

COCKPIT

HANDLEBAR	FSA Grid Low Riser 800mm/ 35mm	FSA V-Drive Flat 740mm / 31.8mm	Alloy Black Curved 31,8 660mm	ALLOY BLACK
STEM	FSA Grid 50mm/ 35mm / ±6°	FSA V-Drive 60mm/ 31.8mm / ±6°	Adjustable 90mm with Cable Integration	Steam Ahead
GRIPS	ERGON Grip GA30 Black - MTB	ERGON Grip GA30 Black - MTB	Grip GP1-L Nexus/Rohloff 128/93	Grip GA30 BLACK - MTB 128/128

SAFETY & ACCESSORIES

REAR LIGHT	-	YES	-	-
RACK	-	YES	-	-
FRONT LIGHT	LITEMOVE SE-110 with reflector 110 Lux	YES	SPANNINGA Axendo 40 with reflector	AXA Blueline 30 with reflector
MUDGUARD	-	YES	-	-
KICKSTAND	-	YES	-	-
BOTTLE CAGE	-	Not Supplied. Frame prepared for standard.	-	-