



S950 Full Suspension Carbon
£ 4,799



C800 Trekking
£ 2,149



M700 ATB Wild
£ 2,149



B400 Urban Low Step
£ 0

PRODUCT INFORMATION

PAINTING	-	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-
FRAME SIZES	-	-	S-M (42) - L/XL (46)	-
MAXIMUM BIKE & RIDER WEIGHT	135kg	120 Kg	135Kg	150kg
WEIGHT	Approx. 26 Kg	Approx. 28 Kg	Approx. 27Kg	Approx. 21 Kg
COLOUR(s)	-	-	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish	-

FRAME

FRAME	Full Carbon FS Frame 140mm	28" TREKKING FRAME	MTB Hardtail Aluminum	28" Aluminium Low Step Frame
SUSPENSION	Rockshox Pike Select 29" Travel 140mm Axel Boost 110mm	-	Rockshox 35S Travel 120mm Axel Boost 110mm 27.5"/29"	-
HEADSET	FSA HS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	Semi integrated 1-1/8"
REAR SHOCK	ROCKSHOX Deluxe Select+ Trunnium 55mm	-	-	-
FORK	-	Rigid Alloy Fork 28" 463mm thru15 OLD 100mm	-	Alloy Fork 28"

DRIVETRAIN & BRAKES

BRAKES	MAGURA Hydraulic MT5	SHIMANO Hydraulic MT200 - FRONT 180mm - REAR 180mm	SHIMANO Hydraulic MT400	ALHONGA Hydraulic Disc HJ-HT474
BRAKE ROTOR - Front	MAGURA MDR-C 203mm	-	SHIMANO SM-RT30 203mm	-
BRAKE ROTOR - Rear	MAGURA MDR-C 203mm	-	SHIMANO SM-RT30 180mm	-
SHIFTERS	-	SHIMANO SHIFT LEVER, SL-M6000-R, DEORE, RIGHT, REAR 10-SPEED RAPIDFIRE PLUS	SRAM NX 11S	SHIMANO Altus SL-M2010
REAR DERRAILEUR	SRAM NX EAGLE 1x12	SHIMANO RD-M6000 DEORE GS 10-SPEED SHADOW PLUS DESIGN DIRECT ATTACHMENT FOR CS	SRAM NX 1x11 Speed	SHIMANO Altus RD-M2000 9S
CASSETTE	-	SHIMANO DEORE CS-HG500-10 10-SPEED	SRAM Power Glid 1130 11-42	SHIMANO CS-HG201 9S
CHAINRING	MIRANDA ChainFlow 3D BCD104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow BCD104 38T
CRANK	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/0	MIRANDA PSI 170/12
CHAIN/BELT DRIVE	SRAM SX EAGLE 12S	SHIMANO CN-E6090-10 FOR E-BIKE REAR 10 SPEED/FRONT SINGLE	KMC E11 Turbo e-bike series	SHIMANO CN-HG53
BRAKE ROTOR	-	SHIMANO SM-RT10 180mm	-	ALHONGA HJ-DXR1806 180MM

E-BIKE SYSTEM

DRIVE UNIT	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S 90Nm	BROSE DRIVE S MAG Horizontal 90Nm	BAFANG H400B 45Nm; Rear Wheel Motor
BATTERY	BROSE 630Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable
BATTERY LOCK KEY	Yes	Yes	Yes	No
CHARGER	4A - 4 hours total charge time	4A charger - 4 hours total charge time	4A - 3,6 hours total charge time	2A - 5 hours total charge time
DISPLAY	BROSE Display Remote	Brose Display Allround	Brose Display Allround	BAFANG LCD Display DPC11

WHEELSET

TYRES	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	CONTINENTAL Tire 29x2,00 Double Fighter III	MAXXIS Rekon S - 27,5x2,6 / M - L/XL- 29x2,4 Black 60 TPI	CONTINENTAL Tire 28x2,00 Contact Cruiser
WHEEL SIZE	Mullet: 27,5 / 29	29X2,00	27,5" (S) / 29" (M-L/XL)	28x2,00
RIMS	Alloy Double Wall Rim Front: 30/ Rear: 35	ALLOY DOUBLE WALL RIM 36 HOLES	Alloy Double Wall Rim 30mm	Alloy double wall rim
SPOKES	Stainless Steel Black	BLACK STEEL SPOKES	Stainless Steel Black	Stainless steel
FRONT HUB	-	SHIMANO HB-MT400 CENTER LOCK DISC 36H FOR 15MM THRU TYPE AXLE OLD	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	Alloy quick release M9x100
REAR HUB	-	SHIMANO FH-M6000 DEORE FOR CENTER LOCK DISC10-SPEED 36H OLD	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	BAFANG H400B

COCKPIT

HANDLEBAR	FSA Grid Low Riser 800mm/ 35mm	ALLOY Black	FSA V-Drive Flat 740mm / 31.8mm	SATORI Alloy Black Ø31.8mm - 660mm
STEM	FSA Grid 50mm/ 35mm / ±6°	Steam Ahead	FSA V-Drive 60mm/ 31.8mm / ±6°	SATORI Ahead Adjustable 0-90°
GRIPS	ERGON Grip GA30 Black - MTB	Grip GA30 BLACK - MTB 128/128	ERGON Grip GA30 Black - MTB	HERRMANS DD36 Ergonomic

SAFETY & ACCESSORIES

REAR LIGHT	-	-	YES	-
RACK	-	-	YES	-
FRONT LIGHT	LITEMOVE SE-110 with reflector 110 Lux	AXA Blueline 30 with reflector	YES	AXA Ecoline 15 with reflector
MUDGUARD	-	-	YES	-
KICKSTAND	-	-	YES	-
BOTTLE CAGE	-	-	Not Supplied. Frame prepared for standard.	-