



G400 Gravel
£ 1,799



E800 Urban Motion Lite
£ 2,199



B400 Urban Low Step
£ 0



M850 Full Suspension
£ 3,699

PRODUCT INFORMATION

FRAME SIZES	-	S (45) - M (50) - L (55)	-	-
MAXIMUM BIKE & RIDER WEIGHT	150kg	120 Kg	150kg	135kg
WEIGHT	Approx. 19 Kg	Approx. 28 Kg	Approx. 21 Kg	Approx. 26 Kg

FRAME

FRAME	28" Aluminium Frame	28" Aluminium Wave Frame	28" Aluminium Low Step Frame	Full Suspension Aluminium Frame 150mm
SUSPENSION	-	-	-	ROCKSHOX 35 Silver Travel 150mm Axel Boost 110mm
HEADSET	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS	Semi integrated 1-1/8"	ACROS AZX-581 1.5" Tapered SHIS with blocklock 150°
SPACERS	-	-	-	1x10mm + 1x5mm
REAR SHOCK	-	-	-	ROCKSHOX Deluxe Select+ Trunnion 57,5mm
FORK	Rigid Alloy 28"	Rigid Alloy Fork 28"	Alloy Fork 28"	-

DRIVETRAIN & BRAKES

BRAKES	TEKTRO HD-C705 Cable Actuated Hydraulic Road Disc Brake	CLARKS Hydraulic M2	ALHONGA Hydraulic Disc HJ-HT474	Shimano Hydraulic MT200SHIMANO MT520 Double Piston
BRAKE ROTOR - Front	-	-	-	SHIMANO SM-RT30 203mm
BRAKE ROTOR - Rear	-	-	-	SHIMANO SM-RT30 180mm
SHIFTERS	MICROSHIFT SB-M100A Dual Control Levers 10s	SHIMANO SHIFT LEVER SL-C6000-8 NEXUS 8	SHIMANO Altus SL-M2010	SHIMANO Deore M5100 Rapidfire 11s
REAR DERRAILEUR	MICROSHIFT AdventX RD-M6205GM 1x10s, Active Motion RD+ with clutch	No	SHIMANO Altus RD-M2000 9S	SHIMANO Deore M5100 SGS Shadow 11s
CASSETTE	MICROSHIFT AdventX CS-EH104 11-48, 10s	No	SHIMANO CS-HG201 9S	SHIMANO 11-51T 11s
CHAINRING	MIRANDA ChainFlow BCD104 38T	MIRANDA Chainring BCD 104 38T	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow 3D BCD104 36T
CRANK	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/0	MIRANDA PSI 170/12	SHIMANO FC-EM600 165mm
CHAIN/BELT DRIVE	KMC e10 turbo 10s	SHIMANO CN-NX10	SHIMANO CN-HG53	KMC e11 Turbo ept
BRAKE ROTOR	SHIMANO SM-RT26M	SHIMANO SM-RT10 180mm	ALHONGA HJ-DXR1806 180MM	-

E-BIKE SYSTEM

DRIVE UNIT	BAFANG H400B 45N - Rear wheel	BRQSE DRIVE C 50Nm	BAFANG H400B 45Nm; Rear Wheel Motor	SHIMANO EP800 85Nm
BATTERY	36V 360Wh - Integrated on Downtube - Non Removable	504 Wh 36V - Integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable	SHIMANO 630Wh 36V - Integrated on Downtube - Removable
BATTERY LOCK KEY	-	Yes	No	Yes
CHARGER	2A - 5 hours total charge time	2A charger	2A - 5 hours total charge time	2A - 8,7 hours total charge time
DISPLAY	BAFANG LCD Display DP.C11	Brose Display Allround	BAFANG LCD Display DP.C11	SHIMANO E7000 with bluetooth

WHEELSET

TYRES	VITTORIA Terreno Dry 47-622 Gravel	CONTINENTAL Contact Cruiser 28x2,2	CONTINENTAL Tire 28x2,00 Contact Cruiser	CONTINENTAL MountainKing 27,5x2,6 / 29x2,4 TrailKing
WHEEL SIZE	29x1.75	28x2.20	28x2,00	Mullet: 27,5 / 29
RIMS	Alloy double wall rim	ALLOY DOUBLE WALL RIM	Alloy double wall rim	Alloy Double Wall Rim Front: 30/ Rear: 35
SPOKES	Stainless stell	STAINLESS STEEL	Stainless steel	Stainless steel blackStainless Steel Black
FRONT HUB	Alloy quick release M9x100	SHIMANO HB-MT400	Alloy quick release M9x100	Boost 110 Thru-axle 15mm 36H
REAR HUB	BAFANG H400B	SHIMANO NEXUS SG-C6001-8D	BAFANG H400B	Boost 148 Thru-axle 12mm 36H, 5 Pawls & 5 Sealed Bearing

COCKPIT

HANDLEBAR	ZOOM Aluminium gravel handlebar 400mm	ALLOY Black	SATORI Alloy Black Ø31.8mm - 660mm	Aluminium Low Riser 780mm/31.8mm
STEM	AHEAD 100mm alloy black	Steam Ahead	SATORI Ahead Adjustable 0-90°	Black with lock-on
GRIPS	SELLE ITALIA SG tape	Grip GP1-L Nexus/Rohloff 128/93	HERRMANS DD36 Ergonomic	Aluminium 40mm/31,8mm with cable integration

SAFETY & ACESSORIES

FRONT LIGHT	-	AXA Blueline 30 with reflector	AXA Ecoline 15 with reflector	LITEMOVE SE-110 with reflector 110 Lux
SEAT POST	ZOOM Alloy Black Ø31,6mm x 300mm	ALLOY Black	ZOOM Alloy Black Ø31,6mm x 300mm	KindShock Dropper Post Lev Integra 150mm
SEAT CLAMP	-	Seatclamp alloy black with quick release and clamp	Alloy black with screw 34.9mm	Seatclamp alloy black with screw
SADDLE	-	SELLE ROYAL RIO GEL	SELLE ROYAL RIO Gel	SELLE SAN MARCO GND Wide Black
PEDALS	NECO with reflectors	Union Ball Ring with "non-slip" and Reflectors	NECO with reflectors	Flat with reflectors
FRAMELOCK	Not supplied, but compatible.	-	Not suplied. Frame prepared	-

* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.