









) - L (56cm) Okg ainting scratch resistant with rnish Blue m High Step y 28" grated 1-1/8" 4400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7° XLIA SG Tape	S (45cm) - M (50cm) - L (55cm) Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Happy Blue with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90° ERGON GP1	S (42cm) - M (46cm) - L (50cm) Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish Moon Grey Gloss with glossy finish Moon Srey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround	M (44cm) - L (48cm) Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100 AL 660mm / 31.8mm (Curved)
0kg ainting scratch resistant with rnish Blue m High Step y 28" grated 1-1/8" H400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish I White Star with glossy varnish I Happy Blue with matte finish I Black Suit with matte finish I Black Suit with I Black Suit With Fish 15" to 1-1/8" Tapered SHIS I SA 1.5" taper	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (straight)	Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
ainting scratch resistant with mish Blue m High Step y 28" grated 1-1/8" H400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
ainting scratch resistant with mish Blue m High Step y 28" grated 1-1/8" H400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with matte minish Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy Varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
mish Blue m High Step y 28" ggrated 1-1/8" H400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	with Matte or Glossy Varnish Happy Blue with matte finish Black Suit with matte finish Black Suit with slue with matte finish Black Suit with finish Black Suit with FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	with Matte or Glossy Varnish Black Fog with matte minish Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
Blue m High Step y 28" grated 1-1/8" H400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Black Fog with matte minish Moon Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
m High Step y 28" grated 1-1/8" H400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Grey Gloss with glossy finish Aluminium MTB Hardtail Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Blue with matte finish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
y 28" grated 1-1/8" H400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	-Rigid Alloy 28"FSA 1.5" to 1-1/8" Tapered SHISBROSE DRIVE C ALU 50Nm504Wh 36V - Integrated on Downtube- Removable40km to 100kmYes2A - 7 hours total charge timeBROSE AllroundAL 660mm / 31.8mm (Curved)AL 90mm - 31.8mm - adjustable 0-90°	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
y 28" grated 1-1/8" H400B Rear Wheel 45Nm Mh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	-Rigid Alloy 28"FSA 1.5" to 1-1/8" Tapered SHISBROSE DRIVE C ALU 50Nm504Wh 36V - Integrated on Downtube- Removable40km to 100kmYes2A - 7 hours total charge timeBROSE AllroundAL 660mm / 31.8mm (Curved)AL 90mm - 31.8mm - adjustable 0-90°	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
grated 1-1/8" H400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Renovable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
grated 1-1/8" H400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Renovable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	- FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
4400B Rear Wheel 45Nm Wh - Integrated on Downtube novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
Wh - Integrated on Downtube novable 100km urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
Wh - Integrated on Downtube novable 100km urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
Wh - Integrated on Downtube novable 100km urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
novable 100km urs total charge time DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	- Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
urs total charge time DRC11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	Yes 2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Yes 2A - 6 hours total charge time SHIMANO SC-E6100
DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	2A - 7 hours total charge time BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	2A - 6 hours total charge time SHIMANO SC-E6100
DP.C11 avel 400mm / 31.8mm / Flare m - 31.8mm - 7°	BROSE Allround AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	SHIMANO SC-E6100
avel 400mm / 31.8mm / Flare m - 31.8mm - 7º	AL 660mm / 31.8mm (Curved) AL 90mm - 31.8mm - adjustable 0- 90°	FSA V-Drive 740mm / 31.8mm (Straight)	
m - 31.8mm - 7º	AL 90mm - 31.8mm (curved) AL 90mm - 31.8mm - adjustable 0- 90°	(Straight)	AL 660mm / 31.8mm (Curved)
m - 31.8mm - 7º	AL 90mm - 31.8mm (curved) AL 90mm - 31.8mm - adjustable 0- 90°	(Straight)	AL 660mm / 31.8mm (Curved)
	90°		
ALIA SG Tape	ERGON GP1	FSA V-Drive 60mm/ 31.8mm / ±6°	AL 90mm - 31.8mm - adjustable 0- 90º
		ERGON GA30	HERRMANS DD36
Terreno Dry 29''x1,75''	CONTINENTAL Contact Cruiser 28"x2,2"	CONTINENTAL Mountain King 27,5"x2,6"	CONTINENTAL Ride Cruiser 28''x2,0''
	28"	27.5"	28"
ble Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
Steel	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
35mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm
H400B 135mm	SHIMANO Nexus SG-C6001-8D	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO FH-TX505 135mm
Cable Activated Hydraulic	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200
) SM-RT26 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT 180mm
) SM-RT26 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT 160mm
IFT AdventX 10S	-	SHIMANO Deore 10S	SHIMANO Altus 9S
IFT AdventX 10S 11-48T	-	SHIMANO Deore 10S 11-42T	SHIMANO Altus 9S 11-36T
IFT AdventX 10S	SHIMANO Nexus 8	SHIMANO Deore 10S	SHIMANO Altus 9S
ChainFlow BCD104 38T	MIRANDA BCD 104 38T	SAMOX BCD 104 36T	SHIMANO SN-CRE50 38T
A JIS 170			SHIMANO FC-E5010 - 175
			SHIMANO CN-HG53
ANDA	Yes - HEBIE	Yes - FSA	Yes - SKS
	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
			AXA Blueline 30 with reflector
			PICCADILLY with reflector
			ATRANVELO Dux
			SKS Yes
			Not included. Frame not prepared.
hed Sold separately			SELLE ROYAL Rio Gel
ded. Sold separately.			
ALIA Model X Superflow	AL Black 350mm 31.6mm/15mm	/20mm	AL Black 350mm 30,9mm/15mm
LIA Model X Superflow 300mm 31,6mm /15mm	· ·	Alloy DIACK WITH SCREW	Alloy black with quick release
ALIA Model X Superflow 300mm 31,6mm /15mm k with screw	Alloy black with quick release	Union CD 21600 Electrodate and anter	UNION SP-827 Flat with reflectors
\ (\ . Т	ChainFlow BCD104 38T JIS 170 'urbo e-bike series NDA ed. Sold separately. IA Model X Superflow	ChainFlow BCD104 38T MIRANDA BCD 104 38T JIS 170 SAMOX Shape 175/0 'urbo e-bike series SHIMANO CN-NX10 NDA Yes - HEBIE ATRANVELO Tour AVS (max.: 25Kg) AXA Blueline 30 with reflector PICCADILLY with reflector ATRANVELO Dux SKS Yes ed. Sold separately. Not included. Sold separately. JA Model X Superflow SELLE ROYAL Rio Gel 00mm 31,6mm /15mm	ChainFlow BCD104 38TMIRANDA BCD 104 38TSAM0X BCD 104 36TJIS 170SAM0X Shape 175/0SAM0X Shape 175/5'urbo e-bike seriesSHIMANO CN-NX10SHIMANO CN-E6090NDAYes - HEBIEYes - FSA'urbo e-bike seriesATRANVELO Tour AVS (max.: 25Kg)ATRANVELO Tour AVS (max.: 25Kg)AXA Blueline 30 with reflectorAXA Blueline 30 with reflectorAXA Blueline 30 with reflectorPICCADILLY with reflectorAXA Slim with reflectorATRANVELO DuxATRANVELO DuxATRANVELO DuxATRANVELO DuxSKSSKSSKSYes-ed. Sold separately.Not included. Sold separately.Not included. Sold separately.JA Model X SuperflowSELLE ROYAL Rio GelSELLE ROYAL Shadow00mm 31,6mm /15mmAL Black 350mm 31,6mm/15mmFSA Gossamer 350mm 31.6mm /20mm

* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.