



**G400 Gravel**  
£ 1,799



**E800 Urban Motion Lite**  
£ 2,199



**M500 ATB Wild**  
£ 2,349



**C800 Urban Motion**  
£ 2,149

## PRODUCT INFORMATION

FRAME SIZES	-	S (45) - M (50) - L (55)	-	-
MAXIMUM BIKE & RIDER WEIGHT	150kg	120 Kg	120 Kg	120 Kg
WEIGHT	Approx. 19 Kg	Approx. 28 Kg	Approx. 26 Kg	Approx. 28 Kg

## FRAME

FRAME	28" Aluminium Frame	28" Aluminium Wave Frame	27,5" MTB HARDTAIL - 6061 Hydroformed Aluminium	28" Aluminium Wave Frame
SUSPENSION	-	-	SrSuntour RAIDON34 LOR DS Travel 130mm Axel Bost 110mm 27,5"	-
HEADSET	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS
FORK	Rigid Alloy 28"	Rigid Alloy Fork 28"	-	Rigid Alloy Fork 28"

## DRIVETRAIN & BRAKES

BRAKES	TEKTRO HD-C705 Cable Actuated Hydraulic Road Disc Brake	CLARKS Hydraulic M2	Shimano Hydraulic MT200	CLARKS Hydraulic M2
SHIFTERS	MICROSHIFT SB-M100A Dual Control Levers 10s	SHIMANO SHIFT LEVER SL-C6000-8 NEXUS 8	SHIMANO DEORE SL-M6000-R 10 Speed	SHIMANO SHIFT LEVER SL-C6000-8 NEXUS 8
REAR DERRAILEUR	MICROSHIFT AdventX RD-M6205GM 1x10s, Active Motion RD+ with clutch	No	SHIMANO DEORE 1x10 Speed	No
CASSETTE	MICROSHIFT AdventX CS-EH104 11-48, 10s	No	SHIMANO DEORE 10 Speed	No
CHAINRING	MIRANDA ChainFlow BCD104 38T	MIRANDA Chainring BCD 104 38T	MESSINGSCHLAGER SAMOX PD-DM-Gen4 50 36T	MIRANDA Chainring BCD 104 38T
CRANK	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/0	MESSINGSCHLAGER SAMOX Shape 175/5	MESSINGSCHLAGER SAMOX Shape 175/5
CHAIN/BELT DRIVE	KMC e10 turbo 10s	SHIMANO CN-NX10	SHIMANO CN-E6090 10-Speed E-Bike 113 Chain Links	SHIMANO CN-NX10
BRAKE ROTOR	SHIMANO SM-RT26M	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	CLARKS 180 mm
FRONT DERRAILEUR	-	-	Non applicable	-

## E-BIKE SYSTEM

DRIVE UNIT	BAFANG H400B 45N - Rear wheel	BROSE DRIVE C 50Nm	BROSE DRIVE S 90Nm	BROSE DRIVE C 50Nm
BATTERY	36V 360Wh - Integrated on Downtube - Non Removable	504 Wh 36V - Integrated on Downtube - Removable	Snake Battery - 504 Wh 36V - Integrated on Downtube - Removable	504 Wh 36V - Semi-Integrated on Downtube - Removable
BATTERY LOCK KEY	-	Yes	Yes	Yes
CHARGER	2A - 5 hours total charge time	2A charger	2A charger - 7 hours total charge time	4A charger
DISPLAY	BAFANG LCD Display DPC11	Brose Display Allround	Brose Display Allround	Brose Display MARQUARDT

## WHEELSET

TYRES	VITTORIA Terreno Dry 47-622 Gravel	CONTINENTAL Contact Cruiser 28x2,2	CONTINENTAL TYRES MOUNTAIN KING 27,5x2,6"	CONTINENTAL Ride Cruiser 28x2,2mm
WHEEL SIZE	29x1.75	28x2.20	27.5x2.6	28x2.2
RIMS	Alloy double wall rim	ALLOY DOUBLE WALL RIM	Double wall aluminium rims	ALLOY DOUBLE WALL RIM
SPOKES	Stainless stell	STAINLESS STEEL	Stainless Steel Black	STAINLESS STEEL
FRONT HUB	Alloy quick release M9x100	SHIMANO HB-MT400	SHIMANO HB-MT400-B	SHIMANO HB-MT400
REAR HUB	BAFANG H400B	SHIMANO NEXUS SG-C6001-8D	SHIMANO FH-M6010-B DEORE	SHIMANO NEXUS SG-C6001-8D

## COCKPIT

HANDLEBAR	ZOOM Aluminium gravel handlebar 400mm	ALLOY Black	FSA V-Drive Flat 740mm / 31.8mm	ALLOY Black
STEM	AHEAD 100mm alloy black	Steam Ahead	FSA V-Drive 60mm/ 31.8mm / ±6°	Steam Ahead
GRIPS	SELLE ITALIA SG tape	Grip GP1-L Nexus/Rohloff 128/93	ERGON GA30 BLACK - MTB 128/128	Grip ERGOTECH EG-AMBITION BLACK

## SAFETY & ACCESSORIES

RACK	-	-	-	ATRANVELO F-Fix Matt Black with clamp with AVS Easy System
FRONT LIGHT	-	AXA BlueLine 30 with reflector	Yes	AXA BlueLine 30 with reflector
SEAT POST	ZOOM Alloy Black Ø31,6mm x 300mm	ALLOY Black	FSA ALLOY	ALLOY Black
SEAT CLAMP	-	Seatclamp alloy black with quick release and clamp	Seatclamp alloy black with screw	Seatclamp alloy black with quick release and clamp
SADDLE	-	SELLE ROYAL RIO GEL	SELLE ROYAL Shadow GEL with Black Guards	SELLE ROYAL RIO GEL
PEDALS	NECO with reflectors	Union Ball Ring with "non-slip" and Reflectors	Union Ball RingCity with Retro Reflectors	Union Ball Ring with "non-slip" and Reflectors
FRAMELOCK	Not supplied, but compatible.	-	-	Not Suplied. Frame prepared

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.