









nish ue n High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm	AL 660mm / 31.8mm (Curved)	S (42cm) - M (46cm) - L (50cm) Approx. 26kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5'' to 1-1/8'' Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	M (44cm) - L (48cm) Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish  Happy Blue with matte finish   Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time SHIMANO SC-E6100
kg inting scratch resistant with nish ue n High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 rel 400mm / 31.8mm / Flare n - 31.8mm - 7°	Approx. 28kg   120kg   Powder Painting Scratch Resistant with Matte or Glossy Varnish   Black Suit with matte finish   Black Suit with matte finish   Aluminium Low Step   -   Rigid Alloy 28"   FSA 1.5" to 1-1/8" Tapered SHIS   SO4Wh 36V - Semi-Integrated on Downtube - Removable   40km to 100km   Yes   4A - 4 to 5 hours total charge time MARQUARDT Display   AL 660mm / 31.8mm (Curved)	Approx. 26kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish  Happy Blue with matte finish   Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
inting scratch resistant with nish ue h High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 vel 400mm / 31.8mm / Flare n - 31.8mm - 7°	Approx. 28kg   120kg   Powder Painting Scratch Resistant with Matte or Glossy Varnish   Black Suit with matte finish   Black Suit with matte finish   Aluminium Low Step   -   Rigid Alloy 28"   FSA 1.5" to 1-1/8" Tapered SHIS   SO4Wh 36V - Semi-Integrated on Downtube - Removable   40km to 100km   Yes   4A - 4 to 5 hours total charge time MARQUARDT Display   AL 660mm / 31.8mm (Curved)	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish  Happy Blue with matte finish   Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
inting scratch resistant with nish ue h High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 vel 400mm / 31.8mm / Flare n - 31.8mm - 7°	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm SO4Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish  Happy Blue with matte finish   Black Suit with matte finish   Black Suit with matter finish   Black Su
nish ue h High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 vel 400mm / 31.8mm / Flare	with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	with Matte or Glossy Varnish White Star with glossy varnish  Happy Blue with matte finish   Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
n High Step 28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 rel 400mm / 31.8mm / Flare	Aluminium Low Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm SO4Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Blue with matte finish   Black Suit with matte finish Aluminium Low Step - Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable D0km rs total charge time P.C11 rel 400mm / 31.8mm / Flare	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable D0km rs total charge time P.C11 rel 400mm / 31.8mm / Flare	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
28" rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable D0km rs total charge time P.C11 rel 400mm / 31.8mm / Flare	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
rated 1-1/8" 400B Rear Wheel 45Nm h - Integrated on Downtube ovable 20km rs total charge time P.C11 /el 400mm / 31.8mm / Flare	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	- FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Acros 1.5" to 1-1/8" Tapered SHIS SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
400B Rear Wheel 45Nm h - Integrated on Downtube ovable D0km rs total charge time P.C11 /el 400mm / 31.8mm / Flare	BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	SHIMANO STEPS E5000 40Nm 418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
h - Integrated on Downtube ovable DOkm rs total charge time P.C11 rel 400mm / 31.8mm / Flare	504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
h - Integrated on Downtube ovable DOkm rs total charge time P.C11 rel 400mm / 31.8mm / Flare	504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
h - Integrated on Downtube ovable DOkm rs total charge time P.C11 rel 400mm / 31.8mm / Flare	504Wh 36V - Semi-Integrated on Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	418Wh 36V - Semi-integrated in downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
ovable D0km rs total charge time P.C11 /el 400mm / 31.8mm / Flare n - 31.8mm - 7°	Downtube - Removable 40km to 100km Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	downtube - Removable 40km to 100km Yes 2A - 6 hours total charge time
rs total charge time P.C11 /el 400mm / 31.8mm / Flare n - 31.8mm - 7º	Yes 4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	Yes 2A - 6 hours total charge time
P.C11 /el 400mm / 31.8mm / Flare n - 31.8mm - 7°	4A - 4 to 5 hours total charge time MARQUARDT Display AL 660mm / 31.8mm (Curved)	2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm	2A - 6 hours total charge time
P.C11 /el 400mm / 31.8mm / Flare n - 31.8mm - 7°	MARQUARDT Display AL 660mm / 31.8mm (Curved)	BROSE Allround FSA V-Drive 740mm / 31.8mm	5
/el 400mm / 318mm / Flare 1 - 318mm - 7º	AL 660mm / 31.8mm (Curved)	FSA V-Drive 740mm / 31.8mm	SHIMANO SC-E6100
n - 31.8mm - 7º	AL 660mm / 31.8mm (Curved)	,	
n - 31.8mm - 7º	AL 660mm / 31.8mm (Curved)	,	
		(Straight)	AL 660mm / 31.8mm (Curved)
IA SG Tane	AL 90mm - 31.8mm - adjustable 0- 90º	FSA V-Drive 60mm/ 31.8mm / ±6°	AL 90mm - 31.8mm - adjustable 0- 90°
	ERGOTECH EG-AMBITION	ERGON GA30	HERRMANS DD36
erreno Dry 29''x1,75''	CONTINENTAL Ride Cruiser 28''x2,2''	CONTINENTAL Mountain King 27,5"x2,6"	CONTINENTAL Ride Cruiser 28''x2,0''
	28"	27,5''	28"
le Wall 25mm	Alloy Double 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
iteel	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
5mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm
400B 135mm	SHIMANO NEXUS SG-C6001 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO FH-TX505 135mm
able Activated Hydraulic	CLARKS Hydraulic M2	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200
SM-RT26 180mm	CL HJ-DXR1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT 180mm
SM-RT26 180mm	CL HJ-DXR1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT 160mm
-T AdventX 10S	-	SHIMANO Deore 10S	SHIMANO Altus 9S
	-		SHIMANO Altus 9S 11-36T
			SHIMANO Altus 9S
			SHIMANO SN-CRE50 38T
	•		SHIMANO FC-E5010 - 175
			SHIMANO CN-HG53
NDA	Tes - HEBIE	Tes - FSA	Yes - SKS
	,		ATRANVELO Tour AVS (max.: 25Kg)
			AXA Blueline 30 with reflector
			PICCADILLY with reflector
			ATRANVELO Dux
			SKS Yes
ed. Sold separately			Not included. Frame not prepared.
		, ,	SELLE ROYAL Rio Gel
IA Model X Superflow			
IA Model X Superflow	AL Black 350mm 27.2mm/15mm	/20mm	AL Black 350mm 30,9mm/15mm Alloy black with quick release
00mm 31,6mm /15mm		, ,	UNION SP-827 Flat with reflectors
00mm 31,6mm /15mm with screw	INITIN SP-827 with ratioctors		Not included. Sold separately.
	00mm 31,6mm /15mm with screw	T AdventX 10S SHIMANO NEXUS 8 ChainFlow BCD 104 38T MIRAND A ChainFlow BCD 104 38T JIS 170 SAMOX Shape 175 urbo e-bike series SHIMANO CN-NX10 NDA Yes - HEBIE ATRANVELO City AVS (max.: 25Kg) AXA Blueline 30 with reflector PICCADILY with reflector ATRANVELO Dux SKS Yes ed. Sold separately. Not included. Sold separately. JA Model X Superflow SELLE ROYAL Rio Gel DOmm 31,6mm /15mm AL Black 350mm 27.2mm/15mm with screw Alloy black with quick release 400 Flat with reflectors UNION SP-827 with reflectors	T AdventX 10SSHIMANO NEXUS 8SHIMANO Deore 10SChainFlow BCD104 38TMIRANDA ChainFlow BCD 104 38TSAM0X BCD 104 36TJIS 170SAM0X Shape 175SAM0X Shape 175/5urbo e-bike seriesSHIMANO CN-NX10SHIMANO CN-E6090NDAYes - HEBIEYes - FSAATRANVELO City AVS (max: 25Kg)AXA Blueline 30 with reflector-PICCADILY with reflector-ATRANVELO Dux-SKS-YesYesYesYesVes SkS-YesYesAt RANVELO DuxSELLE ROYAL Sid separately.Not included. Sold separately.Not included. Sold separately.Model X SuperflowSELLE ROYAL Rio GelSELLE ROYAL ShadowFSA Gossamer 350mm 31.6mm /20mmwith screwAlloy black with quick releaseAlloy black with quick releaseAlloy black with quick release

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.