

**G400 Gravel**

£ 1,799

**E850 Urban Motion**

£ 2,399

**S950 Full Suspension Carbon**

£ 4,799

**B400 Urban Low Step**

£ 0

PRODUCT INFORMATION

MAXIMUM BIKE & RIDER WEIGHT	150kg	145kg	135kg	150kg
WEIGHT	Approx. 19 Kg	26,5kg	Approx. 26 Kg	Approx. 21 Kg

FRAME

FRAME	28" Aluminium Frame	28" Aluminium 6061 Low Step Frame	Full Carbon FS Frame 140mm	28" Aluminium Low Step Frame
SUSPENSION	-	-	Rockshox Pike Select 29" Travel 140mm Axle Boost 110mm	-
HEADSET	Semi integrated 1-1/8"	Acros Cable Integration AZX585 with IPS / ICR / Block Lock 150°	FSA HS 1.5" to 1-1/8" Tapered SHIS	Semi integrated 1-1/8"
REAR SHOCK	-	-	ROCKSHOX Deluxe Select+ Trunnion 55mm	-
FORK	Rigid Alloy 28"	Rigid Alloy Fork 28" with Integrated Cable	-	Alloy Fork 28"

DRIVETRAIN & BRAKES

BRAKES	TEKTRO HD-C705 Cable Actuated Hydraulic Road Disc Brake	SHIMANO Hydraulic MT200	MAGURA Hydraulic MT5	ALHONGA Hydraulic Disc HJ-HT474
BRAKE ROTOR - Front	-	-	MAGURA MDR-C 203mm	-
BRAKE ROTOR - Rear	-	-	MAGURA MDR-C 203mm	-
SHIFTERS	MICROSHIFT SB-M100A Dual Control Levers 10s	SHIMANO Nexus 8	-	SHIMANO Altus SL-M2010
REAR DERRAILEUR	MICROSHIFT AdventX RD-M6205GM 1x10s, Active Motion RD+ with clutch	No	SRAM NX EAGLE 1x12	SHIMANO Altus RD-M2000 9S
CASSETTE	MICROSHIFT AdventX CS-EH104 11-48, 10s	No	-	SHIMANO CS-HG201 9S
CHAINRING	MIRANDA ChainFlow BCD104 38T	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA ChainFlow BCD104 38T
CRANK	MIRANDA PSI 170/12	SHIMANO FC-E6100 175mm	MESSINGSCHLAGER SAMOX Shape 175/0	MIRANDA PSI 170/12
CHAIN/BELT DRIVE	KMC e10 turbo 10s	Chain: SHIMANO NX10	SRAM SX EAGLE 12S	SHIMANO CN-HG53
BRAKE ROTOR	SHIMANO SM-RT26M	SHIMANO SM-RT10 180mm	-	ALHONGA HJ-DXR1806 180MM

E-BIKE SYSTEM

DRIVE UNIT	BAFANG H400B 45N - Rear wheel	SHIMANO Steps E6100 60Nm	BROSE DRIVE S MAG Horizontal 90Nm	BAFANG H400B 45Nm; Rear Wheel Motor
BATTERY	36V 360Wh - Integrated on Downtube - Non Removable	504Wh 36V - Integrated on Downtube - Removable	BROSE 630Wh 36V - Integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable
BATTERY LOCK KEY	-	Yes	Yes	No
CHARGER	2A - 5 hours total charge time	2A Charger - 7 hours total charge time	4A - 4 hours total charge time	2A - 5 hours total charge time
DISPLAY	BAFANG LCD Display D.P.C11	SHIMANO SC-E6100	BROSE Display Remote	BAFANG LCD Display D.P.C11

WHEELSET

TYRES	VITTORIA Terreno Dry 47-622 Gravel	28 x 2,2	SCHWALBE Eddy Current 27,5x2,6 / 29x2,4 Evolution Line Folding	CONTINENTAL Tire 28x2,00 Contact Cruiser
WHEEL SIZE	29x1.75	28"	Mullet: 27,5 / 29	28x2,00
RIMS	Alloy double wall rim	Alloy Double Wall Rim 25	Alloy Double Wall Rim Front: 30/ Rear: 35	Alloy double wall rim
SPOKES	Stainless stell	Stainless Steel Black	Stainless Steel Black	Stainless steel
FRONT HUB	Alloy quick release M9x100	SHIMANO HB-MT400	-	Alloy quick release M9x100
REAR HUB	BAFANG H400B	SHIMANO Nexus SG-C6001-8D	-	BAFANG H400B

COCKPIT

HANDLEBAR	ZOOM Aluminium gravel handlebar 400mm	Alloy Black Curved 31,8 660mm	FSA Grid Low Riser 800mm/ 35mm	SATORI Alloy Black Ø31.8mm - 660mm
STEM	AHEAD 100mm alloy black	Adjustable 90mm with Cable Integration	FSA Grid 50mm/ 35mm / ±6°	SATORI Ahead Adjustable 0-90°
GRIPS	SELLE ITALIA SG tape	Grip GP1-L Nexus/Rohloff 128/93	ERGON Grip GA30 Black - MTB	HERRMANS DD36 Ergonomic

SAFETY & ACCESSORIES

FRONT LIGHT	-	SPANNINGA Axendo 40 with reflector	LITEMOVE SE-110 with reflector 110 Lux	AXA Ecoline 15 with reflector
SEAT POST	ZOOM Alloy Black Ø31,6mm x 300mm	Alloy Black	KindShock Dropper Post Lev Integra 150mm	ZOOM Alloy Black Ø31,6mm x 300mm
SEAT CLAMP	-	Seatclamp alloy black with quick release	Seatclamp alloy black with screw	Alloy black with screw 34.9mm
SADDLE	-	SELLE ROYAL Rio Gel	SELLE SAN MARCO GND Wide Black	SELLE ROYAL RIO Gel
PEDALS	NECO with reflectors	UNION non-slip with reflector	Flat Pedal in Aluminium with reflectors	NECO with reflectors
FRAMELOCK	Not supplied, but compatible.	Yes - AXA Block XXL	-	Not suplied. Frame prepared

* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.