



**E850 Trekking Low Step**  
£ 2,399



**C800 Trekking**  
£ 0



**M700 Wild**  
£ 2,599

## PRODUCT INFORMATION

FRAME SIZES	S/M (46cm) - L/XL (54cm)	M (50cm) - L (56cm)	S-M (42cm) - L/XL (46cm)
WEIGHT	26,5kg	Approx. 27kg	Approx. 26Kg
MAXIMUM BIKE & RIDER WEIGHT	145kg	120kg	135Kg
PAINTING	-	-	Powder Painting Scratch Resistant with Matte Varnish
COLOUR(s)	White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish	White Star with glossy varnish   Happy Blue with matte finish   Black Suit with matte finish	-

## FRAME

FRAME	Aluminium Low Step	Aluminium High Step	MTB Hardtail Aluminium
SUSPENSION	Sr Suntour Mobie E25 Air 75mm	-	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29"
FORK	-	Rigid Alloy 28"	-
HEADSET	ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS

## E-BIKE SYSTEM

DRIVE UNIT	SHIMANO Steps E6100 60Nm	BROSE DRIVE S ALU 90Nm	BROSE DRIVE S MAG Horizontal 90Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Semi-integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	Yes	Yes	Yes
CHARGER	2A - 7 hours total charge time	4A - 3 to 6 hours total charge time	4A - 3,6 hours total charge time
DISPLAY	SHIMANO SC-E6100	BROSE Allround	BROSE Allround

## COCKPIT

HANDLEBAR	AL 680mm / 31.8mm (Straight)	AL 680mm / 31.8mm (Straight)	FSA V-Drive 740mm / 31.8mm (Straight)
STEM	AL 90mm - adjustable 0-90° - with integrated cables	AL 90mm - 31.8mm - adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°
GRIPS	ERGON GA30	ERGON GA30	ERGON GA30

## WHEELSET

TYRES	CONTINENTAL RaceKing 29"x 2,2"	CONTINENTAL Double Fighter III 29"x2,0"	MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4"
WHEEL SIZE	29"	29"	27,5" (S) / 29" (M-L/XL)
RIMS	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)
SPOKES	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
FRONT HUB	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
REAR HUB	SHIMANO Deore M6000 135mm	SHIMANO Deore M6000 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm

## DRIVETRAIN & BRAKES

BRAKES	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT400
BRAKE ROTOR - Front	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 203mm
BRAKE ROTOR - Rear	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 180mm
REAR DERRAILEUR	SHIMANO Deore M5100	SHIMANO Deore 10S	SRAM NX 11S
CASSETTE	SHIMANO Deore CS-M5100-11 11-51T	SHIMANO Deore 10S 11-42T	SRAM Power Glid 1130 11-42
SHIFTERS	SHIMANO Deore 11S	SHIMANO Deore 10S	SRAM NX 11S
CHAINRING	SHIMANO SM-CRE61 38T	SAMOX BCD 104 36T	MIRANDA ChainFlow 3D BCD104 38T
CRANK	SHIMANO FC-E6100 175mm	SAMOX Shape 175/0	SAMOX Shape 170/0
CHAIN	Chain: KMC E11 Turbo e-bike series	SHIMANO CN-E6090	KMC E11 Turbo e-bike series
CHAINGUARD	Yes - SHIMANO	Yes - FSA	Yes - FSA

## SAFETY & ACCESSORIES

RACK	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)	-
FRONT LIGHT	SPANNINGA Axendo 40 with reflector	AXA Blueline 30 with reflector	-
REAR LIGHT	PICCADILLY with reflector	PICCADILLY with reflector	-
KICKSTAND	ATRANVELO Dux	ATRANVELO Dux	-
MUDGUARD	SKS	SKS	-
BELL	-	Yes	-
BOTTLE CAGE	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
SADDLE	SELLE ROYAL Essenza Moderate Black Gel	SELLE ROYAL Essenza Moderate Gel	SELLE SAN MARCO X3 e-bike
SEAT POST	AL Black 350mm 31,6mm/15mm	AL Black 350mm 31,6mm/15mm	FSA Gossamer 31.6mm / 350mm / 20mm
SEAT CLAMP	Alloy black with quick release	Alloy black with quick release	Alloy black with screw
PEDALS	UNION SP 827 Flat with reflectors	UNION SP-827 Flat with reflectors	UNION SP-400 Flat with reflectors
FRAMELOCK	AXA Block XXL	Not included. Sold separately.	Not included. Sold separately.

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.