



**E850 Trekking Low Step**  
£ 2,399



**G400 Gravel**  
£ 1,799



**B400 Urban Low Step**  
£ 0



**C800 Urban Motion**  
£ 2,149

## PRODUCT INFORMATION

MAXIMUM BIKE & RIDER WEIGHT	145kg	150kg	150kg	120 Kg
WEIGHT	26,5 Kg	Approx. 19 Kg	Approx. 21 Kg	Approx. 28 Kg

## FRAME

FRAME	28" Aluminium 6061 Low Step Frame	28" Aluminium Frame	28" Aluminium Low Step Frame	28" Aluminium Wave Frame
SUSPENSION	Sr SUNTOUR Mobie E25 Air spring with lockout Travel 75mm	-	-	-
HEADSET	Acros Cable Integration AZX 585 with IPS / ICR / Block Lock 150°	Semi integrated 1-1/8"	Semi integrated 1-1/8"	FSA 15" to 1-1/8" Tapered SHIS
FORK	-	Rigid Alloy 28"	Alloy Fork 28"	Rigid Alloy Fork 28"

## DRIVETRAIN & BRAKES

BRAKES	SHIMANO Hydraulic MT200	TEKTRO HD-C705 Cable Actuated Hydraulic Road Disc Brake	ALHONGA Hydraulic Disc HJ-HT474	CLARKS Hydraulic M2
SHIFTERS	SHIMANO Deore M5100 11S	MICROSHIFT SB-M100A Dual Control Levers 10s	SHIMANO Altus SL-M2010	SHIMANO SHIFT LEVER SL-C6000-8 NEXUS 8
REAR DERRAILEUR	SHIMANO Deore M5100	MICROSHIFT AdventX RD-M6205GM 1x10s, Active Motion RD+ with clutch	SHIMANO Altus RD-M2000 9S	No
CASSETTE	SHIMANO Deore CS-M5100-11 11-51T	MICROSHIFT AdventX CS-EH104 11-48, 10s	SHIMANO CS-HG201 9S	No
CHAINRING	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow BCD104 38T	MIRANDA Chainring BCD 104 38T
CRANK	SHIMANO FC-E6100 175mm	MIRANDA PSI 170/12	MIRANDA PSI 170/12	MESSINGSCHLAGER SAMOX Shape 175/5
CHAIN/BELT DRIVE	Chain: KMC E11 Turbo e-bike series	KMC e10 turbo 10s	SHIMANO CN-HG53	SHIMANO CN-NX10
BRAKE ROTOR	SHIMANO SM-RT10 180mm	SHIMANO SM-RT26M	ALHONGA HJ-DXR1806 180MM	CLARKS 180 mm

## E-BIKE SYSTEM

DRIVE UNIT	SHIMANO Steps E6100 60Nm	BAFANG H400B 45N - Rear wheel	BAFANG H400B 45Nm; Rear Wheel Motor	BROSE DRIVE C 50Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	36V 360Wh - Integrated on Downtube - Non Removable	360Wh 36V - Integrated on Downtube - Non Removable	504 Wh 36V - Semi-Integrated on Downtube - Removable
BATTERY LOCK KEY	Yes	-	No	Yes
CHARGER	2A charger - 7 hours total charge time	2A - 5 hours total charge time	2A - 5 hours total charge time	4A charger
DISPLAY	SHIMANO SC-E6100	BAFANG LCD Display DP:C11	BAFANG LCD Display DP:C11	Brose Display MARQUARDT

## WHEELSET

TYRES	CONTINENTAL RaceKing 29 x 2,2	VITTORIA Terreno Dry 47-622 Gravel	CONTINENTAL Tire 28x2,00 Contact Cruiser	CONTINENTAL Ride Cruiser 28x2,2mm
WHEEL SIZE	29"	29x1.75	28x2,00	28x2.2
RIMS	Alloy Double Wall Rim 25	Alloy double wall rim	Alloy double wall rim	ALLOY DOUBLE WALL RIM
SPOKES	Stainless Steel Black	Stainless stell	Stainless steel	STAINLESS STEEL
FRONT HUB	SHIMANO HB-MT400	Alloy quick release M9x100	Alloy quick release M9x100	SHIMANO HB-MT400
REAR HUB	SHIMANO Deore M6000 135mm	BAFANG H400B	BAFANG H400B	SHIMANO NEXUS SG-C6001-8D

## COCKPIT

HANDLEBAR	Alloy Black Flat 31,8 680mm	ZOOM Aluminium gravel handlebar 400mm	SATORI Alloy Black Ø31.8mm - 660mm	ALLOY Black
STEM	Adjustable 90mm with Cable Integration	AHEAD 100mm alloy black	SATORI Ahead Adjustable 0-90°	Steam Ahead
GRIPS	ERGON GA30 Black - MTB 128/128	SELLE ITALIA SG tape	HERRMANS DD36 Ergonomic	Grip ERGOTECH EG-AMBITION BLACK

## SAFETY & ACCESSORIES

RACK	-	-	-	ATRANVELO F-Fix Matt Black with clamp with AVS Easy System
FRONT LIGHT	SPANNINGA Axendo 40 with reflector	-	AXA Ecoline 15 with reflector	AXA BlueLine 30 with reflector
SEAT POST	Alloy Black	ZOOM Alloy Black Ø31,6mm x 300mm	ZOOM Alloy Black Ø31,6mm x 300mm	ALLOY Black
SEAT CLAMP	Seatclamp alloy black with quick release	-	Alloy black with screw 34.9mm	Seatclamp alloy black with quick release and clamp
SADDLE	SELLE ROYAL Essenza Moderate Man Black Gel	-	SELLE ROYAL RIO Gel	SELLE ROYAL RIO GEL
PEDALS	UNION non-slip with reflectors	NECO with reflectors	NECO with reflectors	Union Ball Ring with "non-slip" and Reflectors
FRAMELOCK	Yes - AXA Block XXL	Not supplied, but compatible.	Not supplied. Frame prepared	Not Suplied. Frame prepared

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.